

FRAME 40 system

recessed with trim


EN Luminaire housing made of extruded aluminium; recessed luminaire with trim; designed for continuous lighting systems; suitable for ceiling thickness of 8-25 mm; surface powder coated; luminaire profile for mounting available in advance; remaining luminaire components mounted without tools; HPO (High Performance Opal) cover in the length of the light inset or continuous cover (both separately available); optional high gloss reflector with faceted design; pre-assembled power rail for power supply in luminaire profile; voltage tap of the light inset on the power rail; light inset consisting of highly reflective coated extruded profile for improved thermal management; energy-efficient LEDs with very good colour rendering; optionally spotlight modules can be installed

DE Leuchtenkörper aus Aluminiumstrangpressprofil; Einbauleuchte mit umlaufendem Rand; ausgelegt für durchgehende Lichtsysteme; geeignet für Deckenstärken von 8-25 mm; Oberfläche pulverbeschichtet; Leuchtenprofil für Montage vorab lieferbar; restliche Leuchtenkomponenten werkzeuglos montierbar; HPO (High Performance Opal) Abdeckung in Lichteinsatzlänge oder durchgängige Abdeckung (beide separat zu bestellen); optional hochglänzender Reflektor mit Facettenoptik; vormontierte Stromschiene zur Spannungsversorgung im Leuchtenprofil; Lichteinsatz-Spannungsabgriff an der Stromschiene; Lichteinsatz bestehend aus hochreflektierend lackiertem Strangpressprofil für verbessertes Thermomanagement; energieeffiziente LEDs mit sehr guter Farbwiedergabe; wahlweise Strahlereinsätze einsetzbar

Quickinfo

3000 K, 4000 K
 CRI ≥ 90, 3 SDCM
 up to 3270 lm/m
 up to 142 lm/W
 L90 @ 50 000 h
 DALI-2
 opal, microprismatic,
 reflector (UGR ≤ 19)

Types



Colours



Light distributions



DiiA® standards
 251, 252, 253




snap-in system
 (patent pending)



DIN EN 12464-1
 UGR ≤ 19



spotlight
 insets



breakable
 flex insets

Order options

LED TYPE	
mid lumen	1
high lumen	2

COLOUR TEMPERATURE	
3000K	0
4000K	1

CONTROL	
DALI-2	


MATERIAL COLOUR	
<input type="radio"/> traffic white RAL 9016	7
<input checked="" type="radio"/> white aluminium RAL 9006	G
<input type="radio"/> jet black RAL 9005	8

MATERIAL COLOUR	
<input type="radio"/> traffic white RAL 9016	W
<input checked="" type="radio"/> white aluminium RAL 9006	G
<input type="radio"/> jet black RAL 9005	8

LENGTH	
1000mm	1
2000mm	2
3000mm	3

LIGHT OPTIC COVER	
opal high performance	H
microprismatic	Z
reflector (UGR ≤ 19)	

LIGHT OPTIC COLOUR	
chrome reflector	R
dark chrome reflector	B



FRAME 40 trim

INSTALLATION CHANNEL

TYPE	L (mm)	ORDER CODE
channel	1000	042-700201 <input checked="" type="checkbox"/>
channel	2000	042-700401 <input checked="" type="checkbox"/>
channel	3000	042-700601 <input checked="" type="checkbox"/>
channel corner 90°/cover	250 x 250	042-700C01 <input checked="" type="checkbox"/>

LIGHT OPTIC COVER 40


TYPE	L (mm)	ORDER CODE
linear cover	see left	006-42L0010 <input checked="" type="checkbox"/>
continuous linear cover	6000	006-2206010 <input checked="" type="checkbox"/>
continuous linear cover	25000	006-2225010 <input checked="" type="checkbox"/>
blind cover	see left	006-42L001B <input checked="" type="checkbox"/>



LIGHT INSET 40

SYSTEM POWER (MID/HIGH LUMEN)	L (mm)	ORDER CODE
12.1/18.5W	1000	042-01A2:37
23.4/36W	2000	042-01A4:37
34/54W	3000	042-01A6:37
12.1/18.5W flex	500-1000	042-01AF:37
23.4/36W flex	1500-2000	042-01AG:37

LED TYPE / COVER	SYSTEM POWER	DELIVERED LM	EFFICACY
mid lumen/opal/4000K	11.7W/m	1470lm/m	128lm/W
high lumen/opal/4000K	18.4W/m	2260lm/m	126lm/W



Reflector Insets

LIGHT INSET 40 REFLECTOR

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
12.2W	3000K	1510lm	500	042-0111:37 <input checked="" type="checkbox"/>
	4000K	1630lm		
24.4W	3000K	3020lm	1000	042-0112:37 <input checked="" type="checkbox"/>
	4000K	3270lm		
36W	3000K	4540lm	1500	042-0113:37 <input checked="" type="checkbox"/>
	4000K	4900lm		
48W	3000K	6050lm	2000	042-0114:37 <input checked="" type="checkbox"/>
	4000K	6530lm		
67W	3000K	8810lm	3000	042-0116:37 <input checked="" type="checkbox"/>
	4000K	9510lm		

Spotlight Insets

see next page

Accessories


END CAPS

TYPE	ORDER CODE
end caps (pair)	042-709001 <input checked="" type="checkbox"/>




POWER FEEDER UNIT

TYPE	ORDER CODE
power feeder unit	042-1093230



LINEAR CONNECTOR

TYPE	ORDER CODE
mechanical linear connector	042-7091110
mechanical & electrical linear connector	042-7091230
opal cover linear connector	042-1091910
microprismatic cover linear connector	042-1091810



MOUNTING BRACKET

TYPE	CEILING THICKNESS (mm)	ORDER CODE
mounting bracket (1 piece)	8-25	042-7092110
mounting bracket (25 pieces)	8-25	042-7092110.25

number of brackets required: length of your system in metres+1

LUMINOUS FLUX value calculated for 4000K, CRI ≥ 90, colour white, cover opal 3000K -5%, microprismatic -11%



SPOTLIGHT insets

profiles 40

EN Cylindrical spotlight made of aluminium; powder coated; spotlight can be installed without tools in MINO 40 system or FRAME 40 system; choice of single lamp or double lamps; spotlight head rotatable (SASSO 40) or rotatable and tiltable (BO); converter in the adapter; high quality, aluminium, vapour deposition coated reflector with faceted design; precise radiation characteristics with different beam angles; optional asym. light distribution; good glare reduction due to recessed light point plane; optical attachments as accessories; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; energy-eff. LEDs - very good colour rendering


DE Zylindrischer Strahler aus Aluminium; pulverbeschichtet; Strahler in MINO 40 system oder FRAME 40 system werkzeuglos einsetzbar; wahlweise einflammig oder zweiflammig; Strahlerkopf drehbar (SASSO 40) bzw. dreh- und schwenkbar (BO); Konverter im Adapter; hochwertiger, aluminiumbedampfter Reflektor mit Facettenoptik; präzise Abstrahlcharakteristik mit verschiedenen Ausstrahlwinkeln; optional asym. Lichtverteilung; gute Entblendung durch zurückversetzte Lichtpunktebene; optische Aufsätze als Zubehör; mit COB (Chip on Board) Technologie für höchste Effizienz; keine Mehrfachschatten; energieeff. LEDs - sehr gute Farbwiedergabe

Quickinfo


3000K, 4000K
 CRI ≥ 90, 2 SDCM
 BO 32 up to 79lm/W
 BO 45 up to 85lm/W
 SASSO 40 up to 84lm/W
 L80 @ 50000h
 DALI-2

Types


BO 32



BO 45



SASSO 40 wallwasher floor



Colours



Light distributions



DiiA® standards
 251, 252, 253



snap-in system
 (patent pending)



wallwasher floor
 360° rotatable



wallwasher
 floor

Order options


COLOUR TEMPERATURE	
3000K	0
4000K	1

CONTROL	
DALI-2	

MATERIAL COLOUR	
○ traffic white RAL 9016	7
● jet black RAL 9005	8

BEAM ANGLE SPOTLIGHT 32	
spot 18°	S
medium 23°	M
flood 37°	F


BEAM ANGLE SPOTLIGHT 45	
spot 14°	S
medium 24°	M
flood 39°	F



BO 32




2 LAMPS	SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
	20.6 W	2 × 810 lm	0 4 2 - 0 6 1 0 :: 3 ▣ ▲



BO 45




1 LAMP	SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
	15 W	spot 1060 lm	0 4 2 - 0 5 2 0 :: 3 ▣ S
	15.9 W	medium, flood 1340 lm	0 4 2 - 0 5 2 0 :: 3 ▣ ▲




2 LAMPS	SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
	30 W	spot 2 × 1060 lm	0 4 2 - 0 6 2 0 :: 3 ▣ S
	32 W	medium, flood 2 × 1340 lm	0 4 2 - 0 6 2 0 :: 3 ▣ ▲

SASSO 40 wallwasher / floor



1 LAMP	SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
	9 W	659 lm	0 4 2 - 0 5 2 0 :: 3 ▣ W



2 LAMPS	SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
	15.9 W	2 × 659 lm	0 4 2 - 0 6 2 0 :: 3 ▣ W

Optical accessories

HONEYCOMB LOUVER

TYPE	Ø-H (mm)	ORDER CODE
BO 32	30-3	0 0 7 - 1 9 6 5 1 6 8
BO 45	42-3	0 0 7 - 1 9 6 5 1 8 8

OVAL LENS

TYPE	Ø-H (mm)	ORDER CODE
BO 32	30-3	0 0 7 - 1 9 6 5 8 6 0
BO 45	42-3	0 0 7 - 1 9 6 5 8 8 0

SOFT LENS

TYPE	Ø-H (mm)	ORDER CODE
BO 32	30-3	0 0 7 - 1 9 6 5 9 6 0
BO 45	42-3	0 0 7 - 1 9 6 5 9 8 0

WALLWASHER LENS

TYPE	Ø-H (mm)	ORDER CODE
BO 32	30-3	0 0 7 - 1 9 6 5 7 6 0
BO 45	42-3	0 0 7 - 1 9 6 5 7 8 0

LUMINOUS FLUX value calculated for 4000K, CRI ≥ 90, colour white, medium 3000K -5%