

MINO 40 flex high lumen

ceiling / suspended system

042-012G037 006-4220010H 042-100401X



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Suspended _____

special colours _____

IP20 _____

4190 lm _____

2100 lm/m _____

LED

3000 K _____

CRI ≥ 90 _____

L90 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 99 , R_r: 91 , R₍₁₋₁₅₎: 89 _____

MR 0.61 _____

MDER 0.55 _____

Optical

High Performance Opal _____

opal (lambertsch) _____

PstLM $\leq 1.0^{1,2}$ _____

SVM $\leq 0.4^{1,2}$ _____

Electrical

DALI-2 _____

220-240 V _____

system 36 W _____

system 116 lm/W³ _____

PC1 _____

18 W/m _____

Physical

length 2000 mm _____

width 40 mm _____


height 65 mm _____

5.5 kg _____

L (mm): 1500 - 2000, breakable every 125mm _____

Luminaire housing made of extruded aluminium profile; angular design; for continuous lighting systems; light tight final end caps made of aluminium (available as an accessory); no visible screws; surface special colours powder coated; for ceiling surface mounting or suspended mounting (1500 mm cable suspension as an accessory); height adjustment without tools; luminaire profile can be pre-mounted; pre-assembled power rail for power supply in luminaire profile; voltage tap of the light inset on the power rail; remaining lamp components mounted without tools; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; internal wiring in light halogen free; incl. DALI-2 converter; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ 2000mm² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



Lighting calculator



MINO 40 flex high lumen

ceiling / suspended system

042-012G037 006-4220010H 042-100401X



Project / Type

Notes

Count / Date

Maintenance Factors

| Operating Time [h] | 10 000 | 20 000 | 30 000 | 40 000 | 50 000 |
|--------------------|------------------------------|--------|-------------------|---------------------------------|--------|
| LLMF | 0.98 | 0.96 | 0.94 | 0.92 | 0.9 |
| LSF | 1 | 1 | 1 | 1 | 1 |
| MF | LMF × RSMF × LLMF × LSF | | RSMF ^a | Room Surface Maintenance Factor | |
| MF | Maintenance Factor | | LLMF | Lamp Lumens Maintenance Factor | |
| LMF ^a | Luminaire Maintenance Factor | | LSF | Lamp Survival Faktor | |

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Fixtures |
|--------------------------------|--------------------|
| B10 | 13 |
| B13 | 17 |
| B16 | 21 |
| B20 | 27 |
| C10 | 21 |
| C13 | 28 |
| C16 | 35 |
| C20 | 45 |

Components

LINEAR COVER

| TYPE | ARTICLE NUMBER(S) |
|---------|-------------------|
| 2000 mm | 006-4220010H |

INSTALLATION CHANNEL

| COLOUR | L-W-H (MM) | ARTICLE NUMBER(S) |
|-----------------|------------|-------------------|
| special colours | 2000-40-65 | 042-100401X |

Mounting accessories

END CAPS

| TYPE | COLOUR | L-W-H (MM) | ARTICLE NUMBER(S) |
|--------|-----------------|------------|-------------------|
| 1 pair | pure white | 65-40-4 | 042-1090017 |
| 1 pair | jet black | 65-40-4 | 042-1090018 |
| 1 pair | white aluminium | 65-40-4 | 042-109001G |
| 1 pair | special colours | 65-40-4 | 042-109001X |
| 1 pair | traffic white | 65-40-4 | 042-109001W |

Mounting accessories

LINEAR CONNECTOR

| TYPE | COLOUR | L-W-H (MM) | ARTICLE NUMBER(S) |
|-------------------------|-----------|------------|-------------------|
| mechanical | jet black | 120-36-14 | 042-7091110 |
| mechanical & electrical | jet black | 120-36-14 | 042-7091230 |

OPAL COVER LINEAR CONNECTOR

| COLOUR | L-W-H (MM) | ARTICLE NUMBER(S) |
|------------|------------|-------------------|
| pure white | 120-36-14 | 042-1091910 |

MICROPRISMATIC COVER LINEAR CONNECTOR

| COLOUR | L-W-H (MM) | ARTICLE NUMBER(S) |
|------------|------------|-------------------|
| pure white | 120-36-14 | 042-1091810 |



MINO 40 flex high lumen

ceiling / suspended system

042-012G037 006-4220010H 042-100401X



Project / Type

Notes

Count / Date

Mounting accessories

CEILING FASTENER

| COLOUR | L-W-H (MM) | ARTICLE NUMBER(S) |
|---------------|------------|-------------------|
| traffic white | 67-31-8 | 050-2041117 |
| jet black | 67-31-8 | 050-2041118 |



CABLE SUSPENSION

| COLOUR | ARTICLE NUMBER(S) |
|--------|-------------------|
| chrome | 005-2152110 |



CANOPY

| COLOUR | ARTICLE NUMBER(S) |
|---------------|-------------------|
| traffic white | 005-2311217 |
| jet black | 005-2311218 |



Electrical accessories

POWER FEEDER UNIT

| L-W-H (MM) | ARTICLE NUMBER(S) |
|------------|-------------------|
| 80-36-17 | 042-1093230 |



Electrical accessories

FEEDER CABLE

| COLOUR | ARTICLE NUMBER(S) |
|------------|-------------------|
| pure white | 005-2412417 |
| jet black | 005-2412418 |

Optical accessories

BLIND COVER

| TYPE | COLOUR | ARTICLE NUMBER(S) |
|---------|-----------------|-------------------|
| 1000 mm | traffic white | 006-4210017B |
| 1000 mm | jet black | 006-4210018B |
| 1000 mm | white aluminium | 006-421001GB |
| 2000 mm | traffic white | 006-4220017B |
| 2000 mm | jet black | 006-4220018B |
| 2000 mm | white aluminium | 006-422001GB |
| 3000 mm | traffic white | 006-4230017B |
| 3000 mm | jet black | 006-4230018B |
| 3000 mm | white aluminium | 006-423001GB |
| 1000 mm | special colours | 006-421001XB |
| 2000 mm | special colours | 006-422001XB |
| 3000 mm | special colours | 006-423001XB |



CONTINUOUS LINEAR COVER

| TYPE | ARTICLE NUMBER(S) |
|----------|-------------------|
| 25000 mm | 006-2225010H |
| 6000 mm | 006-2206010H |

