

MINO 40 high lumen

ceiling / suspended system

042-0126137 006-4230010H 042-100601X



| | |
|----------------|--|
| Project / Type | |
| Notes | |
| Count / Date | |



General

| | |
|---------------------|--|
| Ceiling , Suspended | |
| special colours | |
| IP20 | |
| 6790 lm | |
| 2260 lm/m | |

LED

| | |
|---|--|
| 4000 K | |
| CRI ≥ 90 | |
| L90 / 50000 h | |
| initial MacAdam ≤ 3 SDCM | |
| R _g : 99 , R _r : 92 , R _{t(1-15)} : 90 | |
| MR 0.81 | |
| MDER 0.74 | |

Optical

| | |
|--------------------------|--|
| High Performance Opal | |
| opal (lambertsch) | |
| PstLM ≤ 1.0 ¹ | |
| SVM ≤ 0.4 ¹ | |

Electrical

| | |
|------------------------------|--|
| DALI-2 | |
| 220-240 V | |
| system 54 W | |
| system 126 lm/W ² | |
| PC1 | |
| 18 W/m | |

Physical

| | |
|----------------|--|
| length 3000 mm | |
| width 40 mm | |
| height 65 mm | |
| 5.5 kg | |

Luminaire housing made of extruded aluminium profile; angular design; for continuous lighting systems; light tight final end caps made of aluminium (available as an accessory); no visible screws; surface special colours powder coated; for ceiling surface mounting or suspended mounting (1500 mm cable suspension as an accessory); height adjustment without tools; luminaire profile can be pre-mounted; pre-assembled power rail for power supply in luminaire profile; voltage tap of the light inset on the power rail; remaining lamp components mounted without tools; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; internal wiring in light halogen free; incl. DALI-2 converter; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ Value of containing product at full load (undimmed)
² incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



Lighting calculator

