

# SASSO 60 round wallwasher/floor

semi-recessed  
048-37010177W 002-90743



Project / Type

Notes

Count / Date




|                               |
|-------------------------------|
| General                       |
| Ceiling , Semi-Recessed       |
| rotation 360°                 |
| white , RAL 9016 <sup>1</sup> |
| Inner colour white            |
| IP20                          |
| 1050 lm                       |
| fixture 118 lm/W <sup>2</sup> |

|   |
|---|
| LED   |
| 3000 K  |
| CRI ≥ 90  |
| L85 / 50000 h   |
| initial MacAdam ≤ 3 SDCM  |
| R <sub>g</sub> : 99 , R <sub>r</sub> : 91 , R <sub>t(1-15)</sub> : 89 |
| MR 0.61   |
| MDER 0.55   |


|                          |
|--------------------------|
| Optical                  |
| wallwasher floor         |
| PstLM ≤ 1.0 <sup>3</sup> |
| SVM ≤ 0.4 <sup>3</sup>   |

Cylindrical semi-recessed spotlight made of aluminium; surface white powder coated; Inner colour lacquered in white; 360° rotatable; luminaire housing can be attached to mounting plate without tools by interlock; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; degree of protection IP20; PC2; 220-240 V; incl. DALI-2 converter; flicker-free visual comfort through analogue current control (minimum value 1%); external converter for ceiling insertion, through-wiring suitable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



|               |
|---------------|
| Electrical    |
| DALI-2        |
| 220-240 V     |
| system 10.4 W |
| fixture 8.9 W |
| 36 Vf         |
| 250 mA        |
| PC2           |

|                |
|----------------|
| Physical       |
| diameter 72 mm |
| height 75 mm   |
| 0.51 kg        |

|                       |
|-----------------------|
| Cutout                |
| diameter 60 mm        |
| recessed depth 120 mm |

<sup>1</sup> RAL code  
<sup>2</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.  
<sup>3</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator



# SASSO 60 round wallwasher/floor

semi-recessed  
048-37010177W 002-90743



Project / Type

Notes

Count / Date

## Maintenance Factors

| Operating Time [h] | 10 000                       | 20 000 | 30 000            | 40 000                          | 50 000 |
|--------------------|------------------------------|--------|-------------------|---------------------------------|--------|
| LLMF               | 0.982                        | 0.954  | 0.926             | 0.899                           | 0.873  |
| LSF                | 1                            | 1      | 1                 | 1                               | 1      |
| MF                 | LMF × RSMF × LLMF × LSF      |        | RSMF <sup>a</sup> | Room Surface Maintenance Factor |        |
| MF                 | Maintenance Factor           |        | LLMF              | Lamp Lumens Maintenance Factor  |        |
| LMF <sup>a</sup>   | Luminaire Maintenance Factor |        | LSF               | Lamp Survival Faktor            |        |

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Fixtures |
|--------------------------------|--------------------|
| B10                            | 72                 |
| B16                            | 115                |
| C10                            | 106                |
| C16                            | 170                |

## Components

### POWER SUPPLY

| TYPE | L-W-H (MM) | ARTICLE NUMBER(S) |
|------|------------|-------------------|
| 10 W | 147-33-23  | 002-90743         |



### Optional electrical accessories

#### DIN RAIL POWER SUPPLY

| TYPE  | L-W-H (MM) | ARTICLE NUMBER(S) |
|-------|------------|-------------------|
| 160 W | 72-90-63   | 005-6520210       |



#### DIN RAIL LED DRIVER

| TYPE                           | L-W-H (MM) | ARTICLE NUMBER(S) |
|--------------------------------|------------|-------------------|
| DALI-2   200-1050 mA   2 x 42W | 36-88-59   | 005-6121030       |

