

SASSO 60 round wallwasher/floor

semi-recessed

048-37010174W 002-90743



Project / Type

Notes

Count / Date



| |
|-------------------------------|
| General |
| Ceiling , Semi-Recessed |
| rotation 360° |
| white , RAL 9016 ¹ |
| Inner colour matt silver |
| IP20 |
| 1040 lm |
| fixture 118 lm/W ² |


| |
|---|
| LED |
| 3000 K |
| CRI ≥ 90 |
| L85 / 50000 h |
| initial MacAdam ≤ 3 SDCM |
| R _g : 99 , R _r : 91 , R _{t(1-15)} : 89 |
| MR 0.61 |
| MDER 0.55 |

| |
|--------------------------|
| Optical |
| wallwasher floor |
| PstLM ≤ 1.0 ³ |
| SVM ≤ 0.4 ³ |


Cylindrical semi-recessed spotlight made of aluminium; surface white powder coated; Inner colour lacquered in matt silver; 360° rotatable; luminaire housing can be attached to mounting plate without tools by interlock; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; degree of protection IP20; PC2; 220-240 V; incl. DALI-2 converter; flicker-free visual comfort through analogue current control (minimum value 1%); external converter for ceiling insertion, through-wiring suitable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

| |
|---------------|
| Electrical |
| DALI-2 |
| 220-240 V |
| system 10.4 W |
| fixture 8.9 W |
| 36 Vf |
| 250 mA |
| PC2 |

Light distribution



Product drawing



| |
|----------------|
| Physical |
| diameter 72 mm |
| height 75 mm |
| 0.51 kg |

| |
|-----------------------|
| Cutout |
| diameter 60 mm |
| recessed depth 120 mm |

¹ RAL code
² FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.
³ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

