

SASSO 60 square wallwasher

semi-recessed

048-36011171A 002-90762



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Semi-Recessed
 white , RAL 9016 ¹
 Inner colour black
 IP20
 611 lm
 fixture 76 lm/W²

LED

4000 K
 CRI ≥ 90
 L90 / 50000 h
 initial MacAdam ≤ 3 SDCM
 R_g: 102 , R_f: 93 , R_{f(1-15)}: 92
 MR 0.81
 MDER 0.74

Optical

wallwasher
 PstLM ≤ 1.0 ³
 SVM ≤ 0.4 ³

Electrical

DALI-2
 220-240 V
 system 9.5 W
 fixture 8.1 W
 36 Vf
 250 mA
 PC2

Physical


length 72 mm
 width 72 mm
 height 75 mm
 0.51 kg

Cutout


diameter 60 mm
 recessed depth 120 mm

Square semi-recessed spotlight made of aluminium; surface white powder coated; Inner colour lacquered in black; luminaire housing can be attached to mounting plate without tools by interlock; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; degree of protection IP20; PC2; 220-240 V; incl. DALI-2 converter; flicker-free visual comfort through analogue current control (minimum value 1%); external converter for ceiling insertion, through-wiring suitable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code
² FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.
³ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

