

SASSO 60 round wallwasher/floor

semi-recessed

048-37012119W 002-90742



Project / Type

Notes

Count / Date



| |
|-------------------------------|
| General |
| Ceiling , Semi-Recessed |
| rotation 360° |
| black , RAL 9005 ¹ |
| Inner colour gold |
| IP20 |
| 1030 lm |
| fixture 117 lm/W ² |

| |
|---|
| LED |
| 3500 K |
| CRI ≥ 90 |
| L85 / 50000 h |
| initial MacAdam ≤ 3 SDCM |
| R _g : 96 , R _r : 90 , R _{t(1-15)} : 91 |
| MR 0.74 |
| MDER 0.67 |

| |
|--------------------------|
| Optical |
| wallwasher floor |
| PstLM ≤ 1.0 ³ |
| SVM ≤ 0.4 ³ |


| |
|---------------|
| Electrical |
| non DIM |
| 220-240 V |
| system 10.4 W |
| fixture 8.9 W |
| 36 Vf |
| 250 mA |
| PC2 |

| |
|----------------|
| Physical |
| diameter 72 mm |
| height 75 mm |
| 0.46 kg |


| |
|----------------------|
| Cutout |
| diameter 60 mm |
| recessed depth 85 mm |

Cylindrical semi-recessed spotlight made of aluminium; surface black powder coated; Inner colour lacquered in gold; 360° rotatable; luminaire housing can be attached to mounting plate without tools by interlock; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 3500 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; degree of protection IP20; PC2; 220-240 V; incl. converter, non dimmable; external converter for ceiling insertion, through-wiring suitable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code
² FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.
³ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

