

# SASSO 60 round wallwasher/floor

semi-recessed  
048-37012111W 002-90742



Project / Type

Notes

Count / Date




|                               |
|-------------------------------|
| General                       |
| Ceiling , Semi-Recessed       |
| rotation 360°                 |
| black , RAL 9005 <sup>1</sup> |
| Inner colour black            |
| IP20                          |
| 1020 lm                       |
| fixture 115 lm/W <sup>2</sup> |

|   |
|---|
| LED   |
| 3500 K  |
| CRI ≥ 90  |
| L85 / 50000 h   |
| initial MacAdam ≤ 3 SDCM  |
| R <sub>g</sub> : 96 , R <sub>r</sub> : 90 , R <sub>t1-15</sub> : 91 |
| MR 0.74   |
| MDER 0.67   |

|                          |
|--------------------------|
| Optical                  |
| wallwasher floor         |
| PstLM ≤ 1.0 <sup>3</sup> |
| SVM ≤ 0.4 <sup>3</sup>   |

Cylindrical semi-recessed spotlight made of aluminium; surface black powder coated; Inner colour lacquered in black; 360° rotatable; luminaire housing can be attached to mounting plate without tools by interlock; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 3500 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; degree of protection IP20; PC2; 220-240 V; incl. converter, non dimmable; external converter for ceiling insertion, through-wiring suitable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



|               |
|---------------|
| Electrical    |
| non DIM       |
| 220-240 V     |
| system 10.4 W |
| fixture 8.9 W |
| 36 Vf         |
| 250 mA        |
| PC2           |

|                |
|----------------|
| Physical       |
| diameter 72 mm |
| height 75 mm   |
| 0.46 kg        |

|                      |
|----------------------|
| Cutout               |
| diameter 60 mm       |
| recessed depth 85 mm |

<sup>1</sup> RAL code  
<sup>2</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.  
<sup>3</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator

