

# SASSO 60 round downlight

suspended

048-31701317S



Project / Type	
Notes	
Count / Date	



## General

Ceiling , Suspended	
black , RAL 9005 <sup>1</sup>	
Inner colour white	
IP20	
819 lm	

## LED

4000 K	
CRI ≥ 90	
initial MacAdam ≤ 2 SDCM	
R <sub>g</sub> : 98 , R <sub>f</sub> : 90 , R <sub>(1-15)</sub> : 88	
MR 0.8	
MDER 0.72	

## Optical

spot	
beam angle 15°	
UGR < 19	
PstLM ≤ 1.0 <sup>2</sup>	
SVM ≤ 0.4 <sup>2</sup>	

## Electrical


DALI-2	
220-240 V	
system 10.4 W	
system 79 lm/W <sup>3</sup>	
PC1	
1 DALI Addr.	

## Physical

diameter 72 mm	
height 150 mm	
0.85 kg	

Cylindrical spotlight in die-cast aluminium; surface black powder coated; Inner colour lacquered in white; pendant fitting with 1500mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 15° beam; UGR ≤ 19; degree of protection IP20; PC1; 220-240 V; incl. DALI-2 converter; flicker-free visual comfort through analogue current control (minimum value 1%); converter included in canopy; canopy for through wiring; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

## Installation instructions



## Lighting calculator



SASSO 60

round downlight

suspended

048-31701317S



Project / Type

Notes

Count / Date

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	39
B16	63
B20	78
C10	63
C16	100
C20	125

