

# SASSO 60 base round adjustable 1 lamp

ceiling  
048-31309319F



Project / Type

Notes

Count / Date



### General

Ceiling , Surface

tilt max 30°

rotation 360°

black , RAL 9005 <sup>1</sup>

Inner colour gold

IP20

758 lm

### LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 97 , R<sub>r</sub>: 91 , R<sub>(1-15)</sub>: 87

MR 0.52

MDER 0.47

### Optical

flood

beam angle 40°

UGR ≤ 19 , ≥65° <1500 cd/m²

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

### Electrical

DALI-2

220-240 V

system 10.2 W

system 74 lm/W<sup>3</sup>

PC1

### Physical


length 180 mm

width 80 mm


height 81 mm

0.5 kg

### Light distribution



### Product drawing



<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

### Installation instructions



### Lighting calculator

