

048-31400174F



Ceiling , Surface
tilt max 30°
rotation 360°
white , RAL 9016 ¹
Inner colour matt silver
IP20
1700 lm

3000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R_g: 99, R_f: 90, R₍₁₋₁₅₎: 87
MR 0.6
MDER 0.54

flood
beam angle 40°
UGR ≤ 19, ≥65° <1500 cd/m²
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

non DIM
220-240 V
system 20.5 W
system 83 lm/W ³
PC1

length 260 mm
width 80 mm
height 81 mm
0.75 kg

SASSO 60 base round adjustable 2 lamps

ceiling
048-31400174F



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.964	0.923	0.884	0.847	0.811
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF ^a	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF ^a	Luminaire Maintenance Factor		LSF	Lamp Survival Faktor	

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	39
B13	63
B16	79
C10	63
C13	101
C16	126

