

SASSO 60 round
adjustable
ceiling
048-31109171W



Project / Type _____

Notes _____

Count / Date _____



General	
Ceiling , Surface	_____
tilt max 30°	_____
rotation 360°	_____
white , RAL 9016 ¹	_____
Inner colour black	_____
IP20	_____
779 lm	_____


LED	
2700 K	_____
CRI ≥ 90	_____
L80 / 50000 h	_____
initial MacAdam ≤ 2 SDCM	_____
R _g : 97 , R _r : 91 , R ₍₁₋₁₅₎ : 87	_____
MR 0.52	_____
MDER 0.47	_____

Optical	
wide flood	_____
beam angle 56°	_____
≥65° <3000 cd/m²	_____


Cylindrical surface mounted spotlight in die-cast aluminium; suitable for ceiling mounting; surface white powder coated; Inner colour lacquered in black; 360° rotatable and 30° tiltable; luminaire housing can be attached to mounting plate without tools by interlock; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 56° beam; degree of protection IP20; PC1; 220-240 V; incl. converter, non dimmable; converter integrated into spotlight head; luminaire for through wiring; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Electrical	
non DIM	_____
220-240 V	_____
system 10.2 W	_____
system 76 lm/W ²	_____
PC1	_____

Light distribution



Product drawing



Physical	
diameter 72 mm	_____
height 108 mm	_____
0.5 kg	_____

¹ RAL code
² FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions



Lighting calculator

