

# SASSO 60 round adjustable

ceiling

048-31109117M



Project / Type
Notes
Count / Date



--	--	--	--

## General

Ceiling , Surface
tilt max 30°
rotation 360°
black , RAL 9005 <sup>1</sup>
Inner colour white
IP20
874 lm

## LED

2700 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R <sub>g</sub> : 97 , R <sub>r</sub> : 91 , R <sub>(1-15)</sub> : 87
MR 0.52
MDER 0.47

## Optical

medium
beam angle 27°
UGR ≤ 19


## Electrical

non DIM
220-240 V
system 10.2 W
system 86 lm/W <sup>2</sup>
PC1

## Physical

diameter 72 mm
height 108 mm
0.5 kg

## Light distribution



## Product drawing



<sup>1</sup> RAL code  
<sup>2</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

## Installation instructions



## Lighting calculator



SASSO 60 round adjustable ceiling 048-31109117M



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.964	0.923	0.884	0.847	0.811
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF <sup>a</sup>	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF <sup>a</sup>	Luminaire Maintenance Factor		LSF	Lamp Survival Faktor	

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	10
B16	17
B20	20
C10	16
C16	27
C20	33

