


SASSO 60 square downlight

semi-recessed
048-30011111W 002-90790




Square semi-recessed spotlight made of aluminium; surface black powder coated; Inner colour lacquered in black; luminaire housing can be attached to mounting plate without tools by interlock; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 57° beam; degree of protection IP40; PC2; 220-240 V; incl. DALI-2 converter; flicker-free visual comfort through analogue current control (minimum value 1%); external converter for ceiling insertion, through-wiring suitable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



| |
|----------------|
| Project / Type |
| Notes |
| Count / Date |



General

| |
|-------------------------------|
| Ceiling , Semi-Recessed |
| black , RAL 9005 ¹ |
| Inner colour black |
| front IP40 , back IP20 |
| 1040 lm |
| fixture 97 lm/W ² |

LED

| |
|---|
| 4000 K |
| CRI ≥ 90 |
| L80 / 50000 h |
| initial MacAdam ≤ 2 SDCM |
| R _g : 98 , R _f : 90 , R _{t(1-15)} : 88 |
| MR 0.8 |
| MDER 0.72 |

Optical

| |
|-------------------------------|
| wide flood |
| beam angle 57° |
| PstLM ≤ 1.0 ³ |
| SVM ≤ 0.4 ³ |

Electrical

| |
|----------------|
| DALI-2 |
| 220-240 V |
| system 12.5 W |
| fixture 10.6 W |
| 36 Vf |
| 300 mA |
| PC2 |
| 1 DALI Addr. |

Physical

| |
|--------------|
| length 72 mm |
| width 72 mm |
| height 75 mm |
| 0.12 kg |

Cutout

| |
|-----------------------|
| diameter 60 mm |
| recessed depth 120 mm |

¹ RAL code
² FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.
³ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

