

SASSO 100 round wallwasher/floor trimless soft acoustic ceiling

048-2740917W 048-2796197 002-90767



Project / Type _____

Notes _____

Count / Date _____



| |
|---|
| General |
| Ceiling , Recessed |
| rotation 360° |
| white , RAL 9016 ¹ |
| Mounting set signal white for acoustic ceilings |
| IP20 |
| 1910 lm |
| fixture 131 lm/W ² |

| |
|--|
| LED |
| 2700 K |
| CRI ≥ 90 |
| L80 / 50000 h |
| initial MacAdam ≤ 2 SDCM |
| R _g : 97 , R _r : 91 , R ₍₁₋₁₅₎ : 87 |
| MR 0.52 |
| MDER 0.47 |


| |
|--------------------------|
| Optical |
| wallwasher floor |
| PstLM ≤ 1.0 ³ |
| SVM ≤ 0.4 ³ |

| |
|-------------------|
| Electrical |
| DALI-2 |
| 220-240 V |
| system 17.2 W |
| fixture 14.6 W |
| 36 Vf |
| 450 mA |
| PC2 |

| |
|-------------------------------|
| Physical |
| trimless for acoustic ceiling |
| diameter 114 mm |
| height 96 mm |
| 0.72 kg |

| |
|------------------------------|
| Cutout |
| diameter 100 mm |
| min. ceiling thickness 25 mm |
| max. ceiling thickness 40 mm |
| recessed depth 100 mm |

Light distribution



Product drawing



¹ RAL code

² incl. consideration of optical losses & internal control unit losses

³ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

