

048-2740914W 048-2796198 002-90767



Project / Type

## Notes

Count / Date



Ceiling, Recessed  
rotation 360°  
matt silver  
Mounting set traffic black for acoustic ceilings  
IP20  
1910 lm  
fixture 131 lm/W<sup>1</sup>

2700 K
CRI $\geq 90$
L80 / 50000 h
initial MacAdam $\leq 2$ SDCM
R <sub>g</sub> : 97, R <sub>f</sub> : 91, R <sub>{f1-15}</sub> : 87
MR 0.52
MDER 0.47

wallwasher floor
PstLM $\leq 1.0$ <sup>2</sup>
SVM $\leq 0.4$ <sup>2</sup>

DALI-2
220-240 V
system 17.2 W
fixture 14.6 W
36 Vf
450 mA
PC2

trimless for acoustic ceiling
diameter 114 mm
height 96 mm
0.72 kg

diameter 100 mm
min. ceiling thickness 25 mm
max. ceiling thickness 40 mm
recessed depth 100 mm

<sup>1</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses  
SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

<sup>2</sup> Value of containing product at full load (undimmed)

The diagrams show the construction of the number 100 in four different scripts:

- Brahmi:** A symbol consisting of a vertical line with a horizontal bar at the top, and the number 100 written below it.
- Kharosthi:** A symbol consisting of a vertical line with a horizontal bar at the top, and the number 100 written below it.
- Greek:** A symbol consisting of a vertical line with a horizontal bar at the top, and the number 100 written below it.
- Latin:** A symbol consisting of a vertical line with a horizontal bar at the top, and the number 100 written below it.