

SASSO 60 round wallwasher trimless soft acoustic ceiling

048-2641917A 048-2696198 002-90762



Project / Type _____

Notes _____

Count / Date _____



| |
|--|
| General |
| Ceiling , Recessed |
| rotation 360° |
| white , RAL 9016 ¹ |
| Mounting set traffic black for acoustic ceilings |
| IP20 |
| 576 lm |
| fixture 71 lm/W ² |

| |
|---|
| LED |
| 2700 K |
| CRI ≥ 90 |
| L90 / 50000 h |
| initial MacAdam ≤ 3 SDCM |
| R _g : 101 , R _r : 91 , R _{t(1-5)} : 89 |
| MR 0.56 |
| MDER 0.51 |

| |
|--------------------------|
| Optical |
| wallwasher |
| PstLM ≤ 1.0 ³ |
| SVM ≤ 0.4 ³ |

| |
|-------------------|
| Electrical |
| DALI-2 |
| 220-240 V |
| system 9.5 W |
| fixture 8.1 W |
| 36 Vf |
| 250 mA |
| PC2 |
| 1 DALI Addr. |


| |
|-------------------------------|
| Physical |
| trimless for acoustic ceiling |
| diameter 80 mm |
| height 48 mm |
| 0.28 kg |

| |
|------------------------------|
| Cutout |
| diameter 74 mm |
| min. ceiling thickness 25 mm |
| max. ceiling thickness 40 mm |
| recessed depth 120 mm |


¹ RAL code
² incl. consideration of optical losses & internal control unit losses
³ Value of containing product at full load (undimmed)

Round recessed spotlight in die-cast aluminium; 1 lamp; surface white; 360° rotatable; installation without tools in mounting set due to patented ball catch system; round installation housing; traffic black for acoustic ceilings; for trimless installation in soft acoustic ceilings; suitable for ceiling thickness of 25-40 mm; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; PC2; 220-240 V; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Installation instructions



Lighting calculator



SASSO 60 round wallwasher trimless soft acoustic ceiling

048-2641917A 048-2696198 002-90762



Project / Type

Notes

Count / Date

Maintenance Factors

| Operating Time [h] | 10 000 | 20 000 | 30 000 | 40 000 | 50 000 |
|--------------------|------------------------------|--------|-------------------|---------------------------------|--------|
| LLMF | 0.96 | 0.95 | 0.94 | 0.93 | 0.92 |
| LSF | 1 | 1 | 1 | 1 | 1 |
| MF | LMF × RSMF × LLMF × LSF | | RSMF ^a | Room Surface Maintenance Factor | |
| MF | Maintenance Factor | | LLMF | Lamp Lumens Maintenance Factor | |
| LMF ^a | Luminaire Maintenance Factor | | LSF | Lamp Survival Faktor | |

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Fixtures |
|--------------------------------|--------------------|
| B10 | 39 |
| B16 | 63 |
| B20 | 78 |
| C10 | 63 |
| C16 | 100 |
| C20 | 125 |

Components

MOUNTING SET trimless for soft acoustic ceilings

| | | |
|-------------------------------------|--------|-------------------|
| COLOUR | Ø (MM) | ARTICLE NUMBER(S) |
| traffic black for acoustic ceilings | 80 | 048-2696198 |



POWER SUPPLY

| | | |
|------|------------|-------------------|
| TYPE | L-W-H (MM) | ARTICLE NUMBER(S) |
| 28 W | 143-43-30 | 002-90762 |



Mounting accessories

MOUNTING TOOL

| | | |
|---------------|------------|-------------------|
| COLOUR | L-W-H (MM) | ARTICLE NUMBER(S) |
| traffic black | 77-77-35 | 048-2695918 |



Optional electrical accessories

DIN RAIL POWER SUPPLY

| | | |
|-------|------------|-------------------|
| TYPE | L-W-H (MM) | ARTICLE NUMBER(S) |
| 160 W | 72-90-63 | 005-6520210 |



DIN RAIL LED DRIVER

| | | |
|--------------------------------|------------|-------------------|
| TYPE | L-W-H (MM) | ARTICLE NUMBER(S) |
| DALI-2 200-1050 mA 2 x 42W | 36-88-59 | 005-6121030 |

