

SASSO 60 round wallwasher/floor trimless soft acoustic ceiling

048-2641214W 048-2696198 002-90743



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Recessed
 rotation 360°
 matt silver
 Mounting set traffic black for acoustic ceilings
 IP20
 1040 lm
 fixture 118 lm/W¹

LED

3500 K
 CRI ≥ 90
 L85 / 50000 h
 initial MacAdam ≤ 3 SDCM
 R_g: 96 , R_r: 90 , R_{t(1-15)}: 91
 MR 0.74
 MDER 0.67

Optical

wallwasher floor
 PstLM ≤ 1.0²
 SVM ≤ 0.4²

Electrical

non DIM
 220-240 V
 system 10.4 W
 fixture 8.9 W
 36 Vf
 250 mA
 PC2

Physical

trimless for acoustic ceiling
 diameter 80 mm
 height 48 mm
 0.22 kg


Cutout

diameter 74 mm
 min. ceiling thickness 25 mm
 max. ceiling thickness 40 mm
 recessed depth 60 mm


¹ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.
² Value of containing product at full load (undimmed)

Round recessed spotlight in die-cast aluminium; 1 lamp; surface matt silver; 360° rotatable; installation without tools in mounting set due to patented ball catch system; round installation housing; traffic black for acoustic ceilings; for trimless installation in soft acoustic ceilings; suitable for ceiling thickness of 25-40 mm; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 3500 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; PC2; 220-240 V; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Installation instructions



Lighting calculator

