

# SASSO 60 round wallwasher/floor trimless soft acoustic ceiling

048-2641019W 048-2696198 002-90743



Project / Type \_\_\_\_\_  
 Notes \_\_\_\_\_  
 Count / Date \_\_\_\_\_



## General

Ceiling , Recessed \_\_\_\_\_  
 rotation 360° \_\_\_\_\_  
 gold , RAL 260-M <sup>1</sup> \_\_\_\_\_  
 Mounting set traffic black for acoustic ceilings \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 1030 lm \_\_\_\_\_  
 fixture 117 lm/W<sup>2</sup> \_\_\_\_\_

## LED

3000 K \_\_\_\_\_  
 CRI ≥ 90 \_\_\_\_\_  
 L85 / 50000 h \_\_\_\_\_  
 initial MacAdam ≤ 3 SDCM \_\_\_\_\_  
 R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>(1-15)</sub>: 89 \_\_\_\_\_  
 MR 0.61 \_\_\_\_\_  
 MDER 0.55 \_\_\_\_\_

## Optical

wallwasher floor \_\_\_\_\_  
 PstLM ≤ 1.0 <sup>3</sup> \_\_\_\_\_  
 SVM ≤ 0.4 <sup>3</sup> \_\_\_\_\_

## Electrical

non DIM \_\_\_\_\_  
 220-240 V \_\_\_\_\_  
 system 10.4 W \_\_\_\_\_  
 fixture 8.9 W \_\_\_\_\_  
 36 Vf \_\_\_\_\_  
 250 mA \_\_\_\_\_  
 PC2 \_\_\_\_\_

## Physical

trimless for acoustic ceiling \_\_\_\_\_  
 diameter 80 mm \_\_\_\_\_  
 height 48 mm \_\_\_\_\_  
 0.22 kg \_\_\_\_\_


## Cutout

diameter 74 mm \_\_\_\_\_  
 min. ceiling thickness 25 mm \_\_\_\_\_  
 max. ceiling thickness 40 mm \_\_\_\_\_  
 recessed depth 60 mm \_\_\_\_\_


<sup>1</sup> RAL code  
<sup>2</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.  
<sup>3</sup> Value of containing product at full load (undimmed)

Round recessed spotlight in die-cast aluminium; 1 lamp; surface gold; 360° rotatable; installation without tools in mounting set due to patented ball catch system; round installation housing; traffic black for acoustic ceilings; for trimless installation in soft acoustic ceilings; suitable for ceiling thickness of 25-40 mm; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; PC2; 220-240 V; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

