

SASSO 60 round downlight

trim 2 lamps

048-2602914M 048-2698317 002-90790




Project / Type	
Notes	
Count / Date	



Round recessed spotlight in die-cast aluminium; 2 lamps; surface matt silver; installation without tools in mounting set due to patented ball catch system; oval installation housing; with trim traffic white; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 26° beam; UGR ≤ 16 ; degree of protection from below IP44 (from above IP20); PC2; 220-240 V; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Ceiling , Recessed	
rotation 360°	
matt silver	
Mounting set traffic white	
front IP44 , back IP20	
2080 lm	
fixture 98 lm/W ¹	

LED

2700 K	
CRI ≥ 90	
L80 / 50000 h	
initial MacAdam ≤ 2 SDCM	
R _g : 97 , R _r : 91 , R ₍₁₋₁₅₎ : 87	
MR 0.52	
MDER 0.47	

Optical

medium	
beam angle 26°	
UGR ≤ 16	
PstLM ≤ 1.0 ²	
SVM ≤ 0.4 ²	

Electrical

DALI-2	
220-240 V	
system 25.0 W	
fixture 10.6 W	
36 Vf	
300 mA	
fixture 21.3 W	
PC2	
1 DALI Addr.	

Physical

trim	
length 147 mm	
width 80 mm	
height 48 mm	
0.34 kg	

Cutout

diameter 70 mm	
length 70 mm	
width 136 mm	
min. ceiling thickness 2 mm	
max. ceiling thickness 25 mm	
recessed depth 110 mm	

¹ incl. consideration of optical losses & internal control unit losses
² Value of containing product at full load (undimmed)



SASSO 60 round downlight

trim 2 lamps

048-2602914M 048-2698317 002-90790



Project / Type

Notes

Count / Date

Installation
instructions



Lighting
calculator

