

# SASSO 60 round downlight

trimless exposed concrete

048-2602219W 048-2695210 002-90790



Project / Type

Notes

Count / Date



**General**

Ceiling , Recessed

rotation 360°

gold , RAL 260-M <sup>1</sup>

Mounting set white aluminium

front IP44 , back IP20

1040 lm

fixture 98 lm/W<sup>2</sup>

**LED**

3500 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 99 , R<sub>r</sub>: 90 , R<sub>t(1-15)</sub>: 89

MR 0.7

MDER 0.64

**Optical**

wide flood

beam angle 56°

PstLM ≤ 1.0 <sup>3</sup>

SVM ≤ 0.4 <sup>3</sup>

**Electrical**

DALI-2

220-240 V

system 12.5 W

fixture 10.6 W

36 Vf

300 mA

PC2

1 DALI Addr.

**Physical**

trimless for exposed concrete ceiling

length 230 mm

width 230 mm


height 162 mm

2.41 kg


**Cutout**

recessed depth 120 mm

## Light distribution



## Product drawing



<sup>1</sup> RAL code

<sup>2</sup> incl. consideration of optical losses & internal control unit losses

<sup>3</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator

