

# SASSO 60 round wallwasher

semi-recessed  
048-3701111A 002-90748



Project / Type

Notes

Count / Date




General
Ceiling , Semi-Recessed
rotation 360°
black , RAL 9005 <sup>1</sup>
Inner colour black
IP20
594 lm
fixture 73 lm/W <sup>2</sup>

LED
4000 K
CRI ≥ 90
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
R <sub>g</sub> : 102 , R <sub>r</sub> : 93 , R <sub>(1-15)</sub> : 92
MR 0.81
MDER 0.74

Optical
wallwasher
PstLM ≤ 1.0 <sup>3</sup>
SVM ≤ 0.4 <sup>3</sup>

Cylindrical semi-recessed spotlight made of aluminium; surface black powder coated; Inner colour lacquered in black; 360° rotatable; luminaire housing can be attached to mounting plate without tools by interlock; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; degree of protection IP20; PC2; 220-240 V; incl. DALI-2 converter; flicker-free visual comfort through analogue current control (minimum value 1%); external converter for ceiling insertion, through-wiring suitable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



Electrical
DALI-2
220-240 V
system 9.5 W
fixture 8.1 W
36 Vf
250 mA
PC2

Physical
diameter 72 mm
height 75 mm
0.51 kg

Cutout
diameter 60 mm
recessed depth 120 mm

<sup>1</sup> RAL code  
<sup>2</sup> incl. consideration of optical losses & internal control unit losses  
<sup>3</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator

