

SASSO 60 square wallwasher/floor

semi-recessed

048-36012117W 002-90742



Project / Type


Notes

Count / Date



Square semi-recessed spotlight made of aluminium; surface black powder coated; Inner colour lacquered in white; luminaire housing can be attached to mounting plate without tools by interlock; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 3500 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; degree of protection IP20; PC2; 220-240 V; incl. converter, non dimmable; external converter for ceiling insertion, through-wiring suitable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Ceiling , Semi-Recessed
black , RAL 9005 ¹
Inner colour white
IP20
1060 lm
fixture 119 lm/W²

LED

3500 K
CRI ≥ 90
L85 / 50000 h
initial MacAdam ≤ 3 SDCM
R_g: 96 , R_f: 90 , R₍₁₋₁₅₎: 91
MR 0.74
MDER 0.67

Optical

wallwasher floor
PstLM ≤ 1.0 ³
SVM ≤ 0.4 ³

Electrical

non DIM
220-240 V
system 10.4 W
fixture 8.9 W
36 Vf
250 mA
PC2

Physical

length 72 mm
width 72 mm
height 75 mm
0.46 kg

Cutout

diameter 60 mm
recessed depth 85 mm

¹ RAL code
² incl. consideration of optical losses & internal control unit losses
³ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

