

SASSO 60 round wallwasher/floor trimless soft acoustic ceiling

048-2641911W 048-2696198 002-90742



Project / Type _____

Notes _____

Count / Date _____



General
Ceiling , Recessed
rotation 360°
black , RAL 9005 ¹
Mounting set traffic black for acoustic ceilings
IP20
981 lm
fixture 111 lm/W ²

LED
2700 K
CRI ≥ 90
L85 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 101 , R _r : 90 , R ₍₁₋₁₅₎ : 88
MR 0.51
MDER 0.46


Optical
wallwasher floor
PstLM ≤ 1.0 ³
SVM ≤ 0.4 ³

Electrical
non DIM
220-240 V
system 10.4 W
fixture 8.9 W
36 Vf
250 mA
PC2


Physical
trimless for acoustic ceiling
diameter 80 mm
height 48 mm
0.22 kg

Cutout
diameter 74 mm
min. ceiling thickness 25 mm
max. ceiling thickness 40 mm
recessed depth 60 mm

Light distribution



Product drawing



¹ RAL code

² incl. consideration of optical losses & internal control unit losses

³ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

