

# SASSO 60 round wallwasher/floor

trimless exposed concrete  
048-2641911W 048-2695210 002-90742



Project / Type

Notes

Count / Date



|                               |
|-------------------------------|
| General                       |
| Ceiling , Recessed            |
| rotation 360°                 |
| black , RAL 9005 <sup>1</sup> |
| Mounting set white aluminium  |
| IP20                          |
| 981 lm                        |
| fixture 111 lm/W <sup>2</sup> |

|   |
|---|
| LED   |
| 2700 K  |
| CRI ≥ 90  |
| L85 / 50000 h   |
| initial MacAdam ≤ 3 SDCM  |
| R <sub>g</sub> : 101 , R <sub>r</sub> : 90 , R <sub>f(1-5)</sub> : 88 |
| MR 0.51   |
| MDER 0.46   |


|                          |
|--------------------------|
| Optical                  |
| wallwasher floor         |
| PstLM ≤ 1.0 <sup>3</sup> |
| SVM ≤ 0.4 <sup>3</sup>   |

|               |
|---------------|
| Electrical    |
| non DIM       |
| 220-240 V     |
| system 10.4 W |
| fixture 8.9 W |
| 36 Vf         |
| 250 mA        |
| PC2           |


|                                       |
|---------------------------------------|
| Physical                              |
| trimless for exposed concrete ceiling |
| length 230 mm                         |
| width 230 mm                          |
| height 162 mm                         |
| 2.35 kg                               |

|                      |
|----------------------|
| Cutout               |
| recessed depth 60 mm |

## Light distribution



## Product drawing



<sup>1</sup> RAL code  
<sup>2</sup> incl. consideration of optical losses & internal control unit losses  
<sup>3</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator

