

# SASSO 60 round wallwasher trimless soft acoustic ceiling

048-2641911A 048-2696198 002-90748



Project / Type

Notes

Count / Date



General
Ceiling , Recessed
rotation 360°
black , RAL 9005 <sup>1</sup>
Mounting set traffic black for acoustic ceilings
IP20
526 lm
fixture 65 lm/W <sup>2</sup>

LED
2700 K
CRI ≥ 90
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
R <sub>g</sub> : 101 , R <sub>r</sub> : 91 , R <sub>t(1-5)</sub> : 89
MR 0.56
MDER 0.51

Optical
wallwasher
PstLM ≤ 1.0 <sup>3</sup>
SVM ≤ 0.4 <sup>3</sup>

Electrical
DALI-2
220-240 V
system 9.5 W
fixture 8.1 W
36 Vf
250 mA
PC2
1 DALI Addr.


Physical
trimless for acoustic ceiling
diameter 80 mm
height 48 mm
0.28 kg

Cutout
diameter 74 mm
min. ceiling thickness 25 mm
max. ceiling thickness 40 mm
recessed depth 120 mm


<sup>1</sup> RAL code  
<sup>2</sup> incl. consideration of optical losses & internal control unit losses  
<sup>3</sup> Value of containing product at full load (undimmed)

Round recessed spotlight in die-cast aluminium; 1 lamp; surface black; 360° rotatable; installation without tools in mounting set due to patented ball catch system; round installation housing; traffic black for acoustic ceilings; for trimless installation in soft acoustic ceilings; suitable for ceiling thickness of 25-40 mm; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; PC2; 220-240 V; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

