

SASSO 60 round wallwasher/floor

trim 2 lamps

048-2641211W 048-2698317 002-90742



Project / Type	
Notes	
Count / Date	



General

Ceiling , Recessed	
rotation 360°	
black , RAL 9005 ¹	
Mounting set traffic white	
IP20	
2040 lm	
fixture 115 lm/W ²	

LED

3500 K	
CRI ≥ 90	
L85 / 50000 h	
initial MacAdam ≤ 3 SDCM	
R _g : 96 , R _r : 90 , R _{t(1-15)} : 91	
MR 0.74	
MDER 0.67	

Optical

wallwasher floor	
PstLM ≤ 1.0 ³	
SVM ≤ 0.4 ³	

Electrical

non DIM	
220-240 V	
system 20.8 W	
fixture 8.9 W	
36 Vf	
250 mA	
fixture 17.7 W	
PC2	

Physical

trim	
length 147 mm	
width 80 mm	
height 48 mm	
0.16 kg	

Cutout

diameter 70 mm	
length 70 mm	
width 136 mm	
min. ceiling thickness 2 mm	
max. ceiling thickness 25 mm	
recessed depth 90 mm	

Round recessed spotlight in die-cast aluminium; 2 lamps; surface black; 360° rotatable; installation without tools in mounting set due to patented ball catch system; oval installation housing; with trim traffic white; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 3500 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; PC2; 220-240 V; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code

² incl. consideration of optical losses & internal control unit losses

³ Value of containing product at full load (undimmed)



SASSO 60 round wallwasher/floor

trim 2 lamps

048-2641211W 048-2698317 002-90742



Project / Type

Notes

Count / Date

Installation
instructions



Lighting
calculator

