

SASSO 60 round adjustable trimless soft acoustic ceiling


048-2622114M 048-2696197 002-90771



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Recessed
 tilt max 30°
 rotation 360°
 matt silver
 Mounting set signal white for acoustic ceilings
 front IP40 , back IP20
 1120 lm
 fixture 106 lm/W¹

LED

4000 K
 CRI ≥ 90
 L80 / 50000 h
 initial MacAdam ≤ 2 SDCM
 R_g: 98 , R_r: 90 , R_[1-15]: 88
 MR 0.8
 MDER 0.72

Optical

medium
 beam angle 27°
 UGR ≤ 16
 P_{stLM} ≤ 1.0²
 SVM ≤ 0.4²

Electrical

non DIM
 220-240 V
 system 12.5 W
 fixture 10.6 W
 36 Vf
 300 mA
 PC2

Physical


trimless for acoustic ceiling
 diameter 80 mm
 height 48 mm
 0.22 kg

Cutout


diameter 74 mm
 min. ceiling thickness 25 mm
 max. ceiling thickness 40 mm
 recessed depth 60 mm

Round recessed spotlight in die-cast aluminium; 1 lamp; surface matt silver; 360° rotatable and 30° tiltable; installation without tools in mounting set due to patented ball catch system; round installation housing; signal white for acoustic ceilings; for trimless installation in soft acoustic ceilings; suitable for ceiling thickness of 25-40 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 27° beam; UGR ≤ 16; degree of protection from below IP40 (from above IP20); PC2; 220-240 V; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ incl. consideration of optical losses & internal control unit losses
² Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

