


SASSO 60 round downlight trimless soft acoustic ceiling

048-2602211S 048-2696197 002-90771



Round recessed spotlight in die-cast aluminium; 1 lamp; surface black; installation without tools in mounting set due to patented ball catch system; round installation housing; signal white for acoustic ceilings; for trimless installation in soft acoustic ceilings; suitable for ceiling thickness of 25-40 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3500 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 15° beam; UGR ≤ 13 ; degree of protection from below IP44 (from above IP20); PC2; 220-240 V; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Project / Type	
Notes	
Count / Date	



General

Ceiling , Recessed	
rotation 360°	
black , RAL 9005 ¹	
Mounting set signal white for acoustic ceilings	
front IP44 , back IP20	
870 lm	
fixture 80 lm/W ²	

LED

3500 K	
CRI ≥ 90	
initial MacAdam ≤ 2 SDCM	
R _g : 99 , R _f : 90 , R ₍₁₋₁₅₎ : 87	
MR 0.6	
MDER 0.54	

Optical

spot	
beam angle 15°	
UGR ≤ 13	
PstLM ≤ 1.0 ³	
SVM ≤ 0.4 ³	

Electrical

non DIM	
220-240 V	
system 12.8 W	
fixture 10.9 W	
36 Vf	
300 mA	
PC2	

Physical

trimless for acoustic ceiling	
diameter 80 mm	
height 48 mm	
0.22 kg	

Cutout

diameter 74 mm	
min. ceiling thickness 25 mm	
max. ceiling thickness 40 mm	
recessed depth 60 mm	

¹ RAL code
² incl. consideration of optical losses & internal control unit losses
³ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

