

UNICO

wall surface


EN Rectangular wall surface mounted multi-uplight made of aluminium; equipped with one light inset (1 lamp) / two (2 lamps) / four (4 lamps) light insets; luminaire housing can be attached to mounting plate without tools by interlock; converter integrated into luminaire housing; surface powder coated; high-quality reflector with micro-faceted, aluminum-vaporised surface; homogeneous wall or ceiling illumination through uniform light distribution; energy-efficient high power LEDs with very good colour rendering; luminaire for through wiring

ES Uplight múltiple de superficie rectangular de aluminio; con uno (1 LAMP) / dos (2 LAMPS) / cuatro (4 LAMPS) insertos lumin.; cuerpo de luminaria enclavable en placa de montaje sin necesidad de herramienta; convertidor integrado en cuerpo de luminaria; superficie con recubrimiento de pintura en polvo; reflector de alta calidad con superficie microfacetada de aluminio vaporizado; iluminación homogénea de pared o techo mediante distribución uniforme de la luz; LEDs de alta eficiencia con muy buena reproducción cromática; luminaria para conexionado adicional

Quickinfo

2700 K, 3000 K, 4000 K
 CRI ≥ 90, 3 SDCM
 up to 47 lm/W
 L90 @ 50 000 h
 non DIM, DALI-2

Types



Colours



Light distribution



ceiling washer



homogeneous ceiling illumination



safety glass for dust protection



tunable white 2700–5000 K

Order options

COLOUR TEMPERATURE ◆◆

2700 K	4
3000 K	5
4000 K	6

CONTROL ◆

non DIM	1
DALI-2	3


MATERIAL COLOUR ◆

○ traffic white RAL 9016	W
● white aluminium RAL 9006	G
● jet black RAL 9005	B

Options on request

COLOUR TEMPERATURE

tunable white 2700–5000K
 only available for 2 lamps and 4 lamps
 DALI-2 DT8




UNICO wall surface




1 LAMP

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
5.8 W	244 lm	090-0L1 :: 1T ■ 001



2 LAMPS


SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
17.3 W	744 lm	090-0L2 :: 2T ■ 001



4 LAMPS

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
29.8 W	1410 lm	090-0L4 :: 4T ■ 001

Light distribution



microprismatic
 direct/indirect power

LUMINOUS FLUX value calculated for
 3000K, CRI ≥ 90, colour white, reflector chrome
 2700K -6%, 4000K +7%