

# HEX-O 750

suspended single  
073-6261537P



Proyecto / Tipo
Notas
Cantidad / Fecha



220-240V
X-PERT
UGR ≤ 19
cd/m² ≤ 3000
CRI ≥ 80
1 ADDR.
X-PERT

## General

Techo , Suspendido
blanco , RAL9010 <sup>1</sup>
IP20
4060 lm

## LED

3000 K
IRC ≥ 80
L90 / 50000 h
seguridad fotobio. RG 0 - sin riesgo
MacAdam inicial ≤ 3 SDCM
MR 0.54
MDER 0.49

## Óptico

Microprismatic
microprismatic
UGR < 19 , ≥ 65° < 3000 cd/m²
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>


## Eléctrico

DALI-2
35 W
CP1 220-240V
116 lm/W
1 DALI Addr.


## Físico

Cable 1500 mm (mín. 500 mm)
length 750 mm
width 650 mm
altura 100 mm
10 kg

## Distribución luminosa



## Diseño del producto



<sup>1</sup> Código RAL  
<sup>2</sup> Valor del producto continente a plena carga (no atenuado)

## Instrucciones de montaje



## Calculadora de iluminación

