

# VELA 600 direct / indirect power

suspended  
073-1454538K



Proyecto / Tipo
Notas
Cantidad / Fecha



## General

Techo , Suspendido
negro , RAL9005 <sup>1</sup>
IP40
indirecto 1860 lm
direct 4150 lm
total 6010 lm

## LED

3000 K
IRC $\geq 80$
L90 / 50000 h
seguridad fotobio. RG 0 - sin riesgo
MacAdam inicial $\leq 3$ SDCM
MR 0.54
MDER 0.49

## Óptico

Microprismatic
microprismatic
UGR $< 19$ , $\geq 65^\circ$ $< 3000$ cd/m <sup>2</sup>
PstLM $\leq 1.0$ <sup>2</sup>
SVM $\leq 0.4$ <sup>2</sup>

## Eléctrico

DALI-2
sistema 45 W
CP1 220-240V
sistema 134 lm/W <sup>3</sup>
1 DALI Addr.

## Físico


varilla 1000 mm
diámetro 600 mm
altura 87 mm
6.1 kg

<sup>1</sup> Código RAL


<sup>2</sup> Valor del producto continente a plena carga (no atenuado)

<sup>3</sup> incl. optical losses and the efficiency of the operating device (converter)

## Distribución luminosa



## Diseño del producto



## Instrucciones de montaje



## Calculadora de iluminación

