

## TASK S system

suspended


**EN** Luminaire housing made of aluminium – rounded edges; rectangular, L-shaped or quarter circle segment design; ultra low-profile design (only 15 mm); for lighting systems; powder coated; cable suspension, tool-less height adjustment; convenient quick mounting system without tools; direct or direct/indirect light distribution by LGP body (Light Guiding Prism); side coupled light, directed downwards or up and down by laser engraving; light control via highly reflective reflector material; optional: indirect component – special PCBs for increased luminous flux (max. ceiling illumination); completely homogeneous illumination; energy-eff. LEDs – very good colour rendering; canopy for through wiring; sound absorb. accessories available

**ES** Cuerpo de aluminio - bordes redond.; rectangular, en L o segmento 1/4 de círculo; perfil extraplano (sólo 15 mm); para sistemas de ilumin.; recubr. de pintura en polvo; suspensión por cable de altura regulable sin herram.; sistema montaje rápido sin herram.; distribución de luz directa o dir./indir. por cuerpo LGP (Light Guiding Prism); la luz acoplada lateralmente se orienta hacia abajo o hacia arriba/abajo por un grabado láser; direccion. de luz por elemento altamente reflectante; opcional: comp. luz indir. – plet. propias para más flujo luminoso (máx. alumbr. del techo); iluminación totalm. homogénea; LED energét. efíc. – excelente reprod. crom.; remate de techo para cableado; accesorio absorbedor del ruido disponible

### Quickinfo

3000 K, 4000 K, TW  
 CRI ≥ 80, CRI ≥ 90, 3 SDCM  
 UGR ≤ 19 / 65° ≤ 3000 cd/m<sup>2</sup>  
 up to ↓ 8270 / ↑ 4470 lm  
 up to 122 lm/W  
 L90 @ 50 000 h  
 DALI-2, DALI-2 sensor  
 microprismatic (UGR ≤ 19)



### Types



### Colours



### Light distributions




DiiA® standards  
 251, 252, 253



single luminaire  
 (p. 432)



acoustic  
 elements



DIN EN 12464-1  
 UGR ≤ 19




click-  
 system



system  
 connector



tunable white  
 2700–6500 K



CRI ≥ 98  
 XPECTRUM

## Order options

### COLOUR TEMPERATURE

3000K	0
4000K	1
tunable white 2700–6500K*	

\*DALI-2 DT8; CRI≥80

3000K + TW 2700–6500K	
4000K + TW 2700–6500K	

DALI-2 DT8 (separately controllable)

### CONTROL

DALI-2	3
DALI-2 sensor*	7

\*version with sensor: length + 9mm


### MATERIAL COLOUR

○ pure white RAL 9010	7
● jet black RAL 9005	8

## Options on request

### COLOUR RENDERING INDEX

CRI ≥ 80	
CRI ≥ 98 XPECTRUM	



## TASK S LINEAR suspended



### DIRECT

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
12.9W	3000K	1460lm	1180	0 5 9 - 5 7 4 4 :: ▣ ▣ K
	4000K	1550lm		
16.1W	3000K	1820lm	1448	0 5 9 - 5 7 4 5 :: ▣ ▣ K
	4000K	1940lm		
19.3W	3000K	2190lm	1748	0 5 9 - 5 7 4 6 :: ▣ ▣ K
	4000K	2330lm		
25.7W	3000K	2920lm	2315	0 5 9 - 5 7 4 8 :: ▣ ▣ K
	4000K	3110lm		



### DIRECT / INDIRECT SOFT


SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
19.5W	3000K	↓ 1900 / ↑ 327lm	1180	0 5 9 - 5 7 5 4 :: ▣ ▣ K
	4000K	↓ 2020 / ↑ 347lm		
24.4W	3000K	↓ 2380 / ↑ 408lm	1448	0 5 9 - 5 7 5 5 :: ▣ ▣ K
	4000K	↓ 2540 / ↑ 435lm		
29.2W	3000K	↓ 2860 / ↑ 490lm	1748	0 5 9 - 5 7 5 6 :: ▣ ▣ K
	4000K	↓ 3040 / ↑ 521lm		
39W	3000K	↓ 3810 / ↑ 653lm	2315	0 5 9 - 5 7 5 8 :: ▣ ▣ K
	4000K	↓ 4050 / ↑ 695lm		



### DIRECT / INDIRECT POWER

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
42W	3000K	↓ 3190 / ↑ 1680lm	1180	0 5 9 - 5 7 6 4 :: ▣ ▣ K
	4000K	↓ 3400 / ↑ 1790lm		
49W	3000K	↓ 3190lm	1180	0 5 9 - 5 7 D 4 0 :: ▣ ▣ K
	(2×DALI) 2700–6500K	↑ 2090lm		
49W	4000K	↓ 3400lm	1180	0 5 9 - 5 7 D 4 1 :: ▣ ▣ K
	(2×DALI) 2700–6500K	↑ 2090lm		
62W (2×)	2700–6500K	↑ 6060lm	1180	0 5 9 - 5 7 6 4 D :: ▣ ▣ K
53W	3000K	↓ 3990 / ↑ 2100lm	1448	0 5 9 - 5 7 6 5 :: ▣ ▣ K
	4000K	↓ 4250 / ↑ 2230lm		
61W	3000K	↓ 3990lm	1448	0 5 9 - 5 7 D 5 0 :: ▣ ▣ K
	(2×DALI) 2700–6500K	↑ 2610lm		
61W	4000K	↓ 4250lm	1448	0 5 9 - 5 7 D 5 1 :: ▣ ▣ K
	(2×DALI) 2700–6500K	↑ 2610lm		
78W (2×)	2700–6500K	↑ 7570lm	1448	0 5 9 - 5 7 6 5 D :: ▣ ▣ K
63W	3000K	↓ 4790 / ↑ 2520lm	1748	0 5 9 - 5 7 6 6 :: ▣ ▣ K
	4000K	↓ 5100 / ↑ 2680lm		
71W	3000K	↓ 4790lm	1748	0 5 9 - 5 7 D 6 0 :: ▣ ▣ K
	(2×DALI) 2700–6500K	↑ 2940lm		
71W	4000K	↓ 5100lm	1748	0 5 9 - 5 7 D 6 1 :: ▣ ▣ K
	(2×DALI) 2700–6500K	↑ 2940lm		
85W (2×)	2700–6500K	↑ 8530lm	1748	0 5 9 - 5 7 6 6 D :: ▣ ▣ K
84W	3000K	↓ 6390 / ↑ 3360lm	2315	0 5 9 - 5 7 6 8 :: ▣ ▣ K
	4000K	↓ 6800 / ↑ 3580lm		
92W	3000K	↓ 6390lm	2315	0 5 9 - 5 7 D 8 0 :: ▣ ▣ K
	(2×DALI) 2700–6500K	↑ 4180lm		
92W	4000K	↓ 6800lm	2315	0 5 9 - 5 7 D 8 1 :: ▣ ▣ K
	(2×DALI) 2700–6500K	↑ 4180lm		
118W (2×)	2700–6500K	↑ 12120lm	2315	0 5 9 - 5 7 6 8 D :: ▣ ▣ K

## Light distributions



microprismatic  
direct/indirect soft

microprismatic  
direct/indirect power

LUMINOUS FLUX value calculated for  
CRI ≥ 90, colour white, cover microprismatic

## Mounting accessories

see next page

**Order options**

**CORNER**

without power feeder	2
with power feeder	3

**COLOUR TEMPERATURE**

3000K	0
4000K	1

**CONTROL**

DALI-2	
--------	--

**MATERIAL COLOUR**

○ pure white RAL 9010	7
● jet black RAL 9005	8



**Options on request**

**COLOUR RENDERING INDEX**

CRI ≥ 80	
CRI ≥ 98 XPECTRUM	

**TASK S CORNER/CURVE suspended**

incl. cable suspension 1500 mm



	CRI ≥ 90	UGR ≤ 19	cd/m <sup>2</sup> ≤ 3000	RG0 IEC 62471				
--	----------	----------	--------------------------	---------------	--	--	--	--

**DIRECT**

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
15W	3000K	1700lm	765	0 5 9 - 5 8 4   3  K
corner	4000K	1810lm		
12.9W	3000K	1460lm	765	0 5 9 - 5 5 4 2   3  K
curve	4000K	1550lm		

	CRI ≥ 90	UGR ≤ 19	cd/m <sup>2</sup> ≤ 3000	RG0 IEC 62471				
--	----------	----------	--------------------------	---------------	--	--	--	--

**DIRECT / INDIRECT SOFT**

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
22.7W	3000K	↓ 2220/↑ 381lm	765	0 5 9 - 5 8 5   3  K
corner	4000K	↓ 2370/↑ 407lm		


	CRI ≥ 90	UGR ≤ 19	RG0 IEC 62471				
--	----------	----------	---------------	--	--	--	--

**DIRECT / INDIRECT POWER**

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
49W	3000K	↓ 3680/↑ 1890lm	765	0 5 9 - 5 8 6   3  K
corner	4000K	↓ 3920/↑ 2010lm		
42W	3000K	↓ 3150/↑ 1610lm	765	0 5 9 - 5 5 6 2   3  K
curve	4000K	↓ 3350/↑ 1720lm		


**Mounting accessories**

**LINEAR/CORNER 90° CONNECTOR** incl. cable suspension 1500 mm




TYPE	L (mm)	ORDER CODE
linear mechanical & electrical	10	0 5 9 - 2 7 9 2 3 1
linear mechanical	10	0 5 9 - 2 7 9 2 4 1
corner 90° mechanical & electrical	254x254	0 5 9 - 2 7 9 2 7 1
corner 90° mechanical	254x254	0 5 9 - 2 7 9 2 8 1

**SYSTEM CONNECTOR** incl. cable suspension 1500 mm



TYPE	L (mm)	ORDER CODE
mechanical & electrical	800	0 5 9 - 2 7 9 2 3 2
mechanical & electrical	1200	0 5 9 - 2 7 9 2 3 3
mechanical & electrical cuttable	1200	0 5 9 - 2 7 9 2 3 0
mechanical & electrical cuttable	2400	0 5 9 - 2 7 9 2 3 4
optional cable suspension	1500	0 5 9 - 2 7 9 2 1 2 7


**Light distributions**



microprismatic  
direct/indirect soft

microprismatic  
direct/indirect power

**END PIECE** incl. cable suspension 1500 mm



TYPE	L (mm)	ORDER CODE
end piece	1500	0 5 9 - 2 7 9 2 1 1

**POWER FEEDER** incl. cable suspension 1500 mm and canopy/feeder cable

TYPE	L (mm)	ORDER CODE
power feeder 5x1.5mm <sup>2</sup>	1500	0 5 9 - 2 7 9 2 2 1
middle power feeder 5x1.5mm <sup>2</sup>	1500	0 5 9 - 2 7 9 2 5 1

for electrical system configuration see luminaire data sheet at xal.com

**LUMINOUS FLUX** value calculated for  
colour white, cover microprismatic