

# TASK direct / indirect soft

free standing T-shape  
059-295315XZ



Proyecto / Tipo	
Notas	
Cantidad / Fecha	



## General

Suelo , De pie	
colores especiales	
IP20	
indirecto 3560 lm	
direct 4370 lm	
total 7930 lm	

## LED

4000 K	
IRC $\geq 90$	
L90 / 50000 h	
MacAdam inicial $\leq 3$ SDCM	
R <sub>g</sub> : 96 , R <sub>f</sub> : 90 , R <sub>t(1-15)</sub> : 87	
MR 0.75	
MDER 0.68	

## Óptico

Microprismatic	
microprismatic	
UGR $\leq 19$	
PstLM $\leq 1.0$ <sup>1</sup>	
SVM $\leq 0.4$ <sup>1</sup>	

## Eléctrico


touch DIM en el poste	
220-240 V	
sistema 71 W	
sistema 112 lm/W <sup>2</sup>	
CP1	

## Físico


T-shape	
longitud 800 mm	
ancho 320 mm	
altura 1920 mm	
13.5 kg	

<sup>1</sup> Valor del producto continente a plena carga (no atenuado)  
<sup>2</sup> incluida la consideración de las pérdidas ópticas, las pérdidas de la unidad de control interno y la eficiencia del dispositivo operativo

## Distribución luminosa



## Diseño del producto



## Instrucciones de montaje

