

LINEA opal / 1 spot

wall

058-6178538CH



Proyecto / Tipo
Notas
Cantidad / Fecha



General

Pared , Superficie
inclinación máx. 89°
negro , RAL 9005 ¹
IP20
172 lm

LED

3000 K
IRC ≥ 97 ² -90 ³
L95 / 50000 h ² -L85 / 50000 h ³
MacAdam inicial ≤ 3 SDCM
R _g : 92 ² -99 ³ , R _f : 86 ² -91 ³ , R _{f(1-15)} : 94 ² -89 ³
MR 0.53 ² -0.61 ³
MDER 0.48 ² -0.55 ³

Óptico

flood ² -opal (lambertsch) ³
ángulo de haz 30°
PstLM ≤ 1.0 ² 3 4
SVM ≤ 0.4 ² 3 4
High Performance Opal


Eléctrico

DALI-2
220-240 V
sistema 2.7 ² -70 ³ W
sistema 64 ² -100 ³ lm/W ⁵
CP1
1 DALI Addr.

Físico

longitud 2510 mm
ancho 40 mm
altura 100 mm
derecha


Distribución luminosa



flood 30° Spot

h (m)	E0° (lx)	ø (m)
1	419	0.54
2	105	1.09
3	47	1.63
4	26	2.17
5	17	2.72

Diseño del producto



¹ Código RAL ² Foco ³ Lineal
⁴ Valor del producto continente a plena carga (no atenuado)
⁵ incluida la consideración de las pérdidas ópticas, las pérdidas de la unidad de control interno y la eficiencia del dispositivo operativo

Instrucciones de montaje

