

MINO 100

suspended


EN Luminaire housing from extruded aluminium profile, angular design; no visible screws; surface powder coated; luminaire profile for mounting available in advance; remaining components mounted without tools; pendant fitting with cable suspension; with integrated tool-less suspension height adjustment; spring clip attachment to the luminaire; freely positionable; with transparent feeder cable; light inset consisting of highly reflective coated extruded profile for improved thermal management; HPO (High Performance Opal) cover for uniform illumination; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; energy-eff. LEDs – very good colour rendering

ES Cuerpo de perfil de aluminio con diseño angular; sin tornillos visibles; superficie con recubrimiento de pintura en polvo; Perfil disponible para pre-montaje; los demás componentes se pueden montar sin herramientas; suspendido con cable; regulación de la altura sin necesitar herramientas; fijación en las lámparas por medio de enganches elásticos; ajustable de una manera sencilla; incl. cable de alimentación transparente; elemento de luz formado por perfil extruido con acabado altamente reflectante para una gestión térmica mejorada; difusor opal de alta calidad que proporciona una iluminación uniforme; cubierta microprismática de PMMA con lámina difusora para la reducción de iluminancia y un alumbrado homogéneo; LED energét. efic. – excelente reprod. crom.

Quickinfo

3000K, 4000K
 CRI ≥ 80, 3 SDCM
 UGR ≤ 19 / 65° ≤ 3000cd/m²
 up to 140lm/W
 L90 @ 50000h
 non DIM, DALI-2
 opal, microprismatic (UGR ≤ 19)

Types




Colours




Light distribution



DiiA® standards
 251, 252, 253




system solution (p.928)



DIN EN 12464-1
 UGR ≤ 19



tunable white
 2700–6500K



CRI ≥ 98
 XPECTRUM

Order options

COLOUR TEMPERATURE	☐☐
3000K	5
4000K	6

CONTROL	⬆️⬆️
non DIM	1
DALI-2	3

MATERIAL COLOUR	☑️
○ pure white RAL 9010	7
● white aluminium RAL 9006	G
● jet black RAL 9005	8


LIGHT OPTIC COVER	☑️
opal high performance	H
microprismatic	Z
microprismatic (UGR ≤ 19)	G

Options on request

COLOUR RENDERING INDEX
CRI ≥ 90
CRI ≥ 98 XPECTRUM

COLOUR TEMPERATURE
tunable white 2700–6500K
DALI-2 DT8

INDIVIDUAL MATERIAL COLOUR
☛ MINO 100 suspended system



MINO 100 suspended




MID LUMEN

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
13W	3000K	1520lm	888	0 5 6 - 4 2 L 3 :: 1 ☑️ ☑️
	4000K	1600lm		
15.3W	3000K	2020lm	1188	0 5 6 - 4 2 L 4 :: 1 ☑️ ☑️
	4000K	2140lm		
19.2W	3000K	2530lm	1488	0 5 6 - 4 2 L 5 :: 1 ☑️ ☑️
	4000K	2670lm		
31W	3000K	4040lm	2360	0 5 6 - 4 2 L 8 :: 1 ☑️ ☑️
	4000K	4280lm		

HIGH LUMEN

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
20.6W	3000K	2510lm	888	0 5 6 - 4 2 M 3 :: ☑️ ☑️ ☑️
	4000K	2650lm		
27.5W	3000K	3340lm	1188	0 5 6 - 4 2 M 4 :: ☑️ ☑️ ☑️
	4000K	3540lm		
34W	3000K	4180lm	1488	0 5 6 - 4 2 M 5 :: ☑️ ☑️ ☑️
	4000K	4420lm		
55W	3000K	6680lm	2360	0 5 6 - 4 2 M 8 :: ☑️ ☑️ ☑️
	4000K	7070lm		

Technical data



MINO 100 suspended, 15.3W, 4000K, direct

ROOM VALUES

Room dimensions	5.4 × 4 × 2.8 m
Reflection factor	0.7 0.5 0.2
Maintenance factor	0.8
Suspension height	2.25 m

CALCULATION SURFACE

Surface dimensions	1.6 × 0.8 m
Surface height	0.75 m
Average illuminance (E _m)	> 500 lx
Uniformity (U ₀)	> 0.6

GLARE EVALUATION

Table Classification X=4H Y=8H S=0.25H	
UGR transversal	≤ 19
UGR axial	≤ 19
≥ 65° ≤ 3000 cd/m²	

LUMINOUS FLUX value calculated for
CRI ≥ 80, colour white, cover opal
microprism. Z -8%, microprism. G -10%