

# JUST 45 MOVE IT 25 / 25 S / 45


050-0131E3XF



Proyecto / Tipo \_\_\_\_\_

Notas \_\_\_\_\_

Cantidad / Fecha \_\_\_\_\_



## General

Techo / Pared , Rail \_\_\_\_\_

inclinable máx 90° \_\_\_\_\_

rotación 360° \_\_\_\_\_

colores especiales \_\_\_\_\_

IP20 \_\_\_\_\_

434 lm \_\_\_\_\_

## LED

colour warm dimming \_\_\_\_\_

2000 K - 3000 K \_\_\_\_\_

CRI ≥ 95 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

MacAdam inicial ≤ 4 SDCM \_\_\_\_\_

R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>f(1-15)</sub>: 90 \_\_\_\_\_

MR 0.61 \_\_\_\_\_

MDER 0.55 \_\_\_\_\_

## Óptico

flood \_\_\_\_\_

ángulo de haz 42° \_\_\_\_\_

## Eléctrico

DALI-2 single control \_\_\_\_\_

11.5 W \_\_\_\_\_

CP3 48V \_\_\_\_\_

38 lm/W \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_


## Físico

diámetro 45 mm \_\_\_\_\_

altura 68 mm \_\_\_\_\_

0.2 kg \_\_\_\_\_


## Distribución luminosa



flood 42°

h (m)	EO° (lx)	ø (m)
1	870	0.77
2	218	1.55
3	97	2.32
4	54	3.10
5	35	3.87

## Diseño del producto



## Instrucciones de montaje

