

TULA micro suspended

canopy trimless

049-5715517F 005-3511017 002-90732



Proyecto / Tipo

Notas

Cantidad / Fecha



General

Techo , Suspendido

blanco , RAL9016 ¹

Baldaquin blanco tráfico

IP20

798 lm

LED

3000 K

IRC \geq 90

L90 / 50000 h

MacAdam inicial \leq 3 SDCM

R_g: 100 , R_f: 90 , R_{f(1-15)}: 87

MR 0.59

MDER 0.54

Óptico

flood

ángulo de haz 44°

PstLM \leq 1.0 ²

SVM \leq 0.4 ²

Eléctrico

non atenuable

sistema 11.3 W

inserto 8.4 W

500 mA

CP2 220-240V

sistema 71 lm/W³

inserto 95 lm/W⁴

Físico

diámetro 47 mm

altura 500 mm

0.71 kg

Orificio

diámetro 65 mm

espesor mín. del techo 9 mm

espesor máx. del techo 25 mm

profundidad empotrada 70 mm


¹ Código RAL

² Valor del producto continente a plena carga (no atenuado)

³ incl. optical losses and the efficiency of the operating device (converter)

⁴ incl. optical losses

Distribución luminosa



flood 44°

h (m)	EO° (lx)	ø (m)
1	1480	0.82
2	370	1.64
3	160	2.45
4	90	3.27
5	60	4.09

Diseño del producto

