

TULA micro suspended

canopy trimless

049-551541XF 005-3511017 002-90733



Proyecto / Tipo _____

Notas _____

Cantidad / Fecha _____



220-240V

UGR ≤ 16

cd/m² ≤ 1500

CRI ≥ 90

X-PERT

General

Techo , Suspendido

colores especiales

Baldaqin blanco tráfico

IP20

694 lm

LED

2700 K

IRC ≥ 90

L90 / 50000 h

MacAdam inicial ≤ 3 SDCM

R_g: 99 , R_r: 91 , R_{t(1-15)}: 89

MR 0.54

MDER 0.49

Óptico

flood

beam angle 44°

PstLM ≤ 1.0 ¹

SVM ≤ 0.4 ¹

Eléctrico

DALI-2

11.3 W

inserto 8.4 W

500 mA

CP2 220-240V

61 lm/W

Físico

diameter 47 mm

altura 300 mm

0.53 kg

Orificio

diameter 65 mm


min. ceiling thickness 9 mm

max. ceiling thickness 25 mm

recessed depth 130 mm

¹ Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



flood 44°

h (m)	EO° (lx)	ø (m)
1	1290	0.82
2	320	1.64
3	140	2.45
4	80	3.27
5	50	4.09

Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

