

TULA micro suspended

canopy trimless

049-5515418M 005-3511017 002-90732



Proyecto / Tipo
Notas
Cantidad / Fecha



220-240V
UGR
cd/m ²
CRI
X-PERT

General

Techo , Suspendido
negro , RAL9005 ¹
Baldaquín blanco tráfico
IP20
648 lm

LED

2700 K
IRC ≥ 90
L90 / 50000 h
MacAdam inicial ≤ 3 SDCM
R _g : 99 , R _r : 91 , R _{t(1-15)} : 89
MR 0.54
MDER 0.49

Óptico

medium
beam angle 25°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Eléctrico

non attenuable
11.3 W
inserto 8.4 W
500 mA
CP2 220-240V
57 lm/W

Físico


diameter 47 mm
altura 300 mm
0.51 kg

Orificio

diameter 65 mm
min. ceiling thickness 9 mm
max. ceiling thickness 25 mm
recessed depth 70 mm

¹ Código RAL
² Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



medium 25°

h (m)	EO° (lx)	ø (m)
1	2800	0.44
2	700	0.89
3	310	1.33
4	180	1.78
5	110	2.22

Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

