

# ARY adjustable rod suspended canopy surface

049-5231418M 005-2602118







Proyecto / Tipo \_\_\_\_\_

Notas \_\_\_\_\_

Cantidad / Fecha \_\_\_\_\_



**General**

Techo , Suspendido \_\_\_\_\_

inclinación máx. 90° \_\_\_\_\_

giro 265° \_\_\_\_\_

negro , RAL9005 <sup>1</sup> \_\_\_\_\_

Baldaquín negro intenso \_\_\_\_\_

IP20 \_\_\_\_\_

642 lm \_\_\_\_\_

**LED**

2700 K \_\_\_\_\_

IRC ≥ 90 \_\_\_\_\_

L90 / 50000 h \_\_\_\_\_

MacAdam inicial ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89 \_\_\_\_\_

MR 0.54 \_\_\_\_\_

MDER 0.49 \_\_\_\_\_

**Óptico**

medium \_\_\_\_\_

ángulo de haz 25° \_\_\_\_\_

**Eléctrico**

non atenuable \_\_\_\_\_

sistema 11.2 W \_\_\_\_\_

inserto 8.4 W \_\_\_\_\_

500 mA \_\_\_\_\_

CP2 220-240V \_\_\_\_\_

sistema 57 lm/W<sup>2</sup> \_\_\_\_\_

inserto 76 lm/W<sup>3</sup> \_\_\_\_\_

**Físico**


varilla 1500 mm con gancho \_\_\_\_\_

diámetro 47 mm \_\_\_\_\_

altura 110 mm \_\_\_\_\_


0.66 kg \_\_\_\_\_

## Distribución luminosa



h (m)	EO° (lx)	ø (m)
1	2780	0.44
2	690	0.89
3	310	1.33
4	170	1.78
5	110	2.22

## Diseño del producto



<sup>1</sup> Código RAL

<sup>2</sup> incl. optical losses and the efficiency of the operating device (converter)

<sup>3</sup> incl. optical losses

## Instrucciones de montaje



## Calculadora de iluminación

