

ARY cable suspended

canopy trim

049-5211617M 005-3521017 002-90733



Proyecto / Tipo
Notas
Cantidad / Fecha



220-240V
UGR
cd/m²
CRI
1ADDR
X-PERT

General

Techo , Suspendido
blanco , RAL9016 ¹
Baldaqin blanco tráfico
IP20
739 lm

LED

4000 K
IRC ≥ 90
L90 / 50000 h
MacAdam inicial ≤ 3 SDCM
R _g : 99 , R _f : 89 , R _{t(1-15)} : 87
MR 0.81
MDER 0.73

Óptico

medium
beam angle 25°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Eléctrico

DALI-2
11.2 W
CP2 220-240V
66 lm/W
1 DALI Addr.

Físico

suspensión 2000 mm con gancho
diameter 47 mm
altura 110 mm
0.6 kg

Orificio

diameter 65 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 130 mm

¹ Código RAL
² Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



medium 25°

h (m)	E0° (lx)	ø (m)
1	3200	0.44
2	800	0.89
3	360	1.33
4	200	1.78
5	130	2.22

Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

