

# ARY adjustable rod suspended canopy surface


049-523151XF 005-2602137



Proyecto / Tipo \_\_\_\_\_

Notas \_\_\_\_\_

Cantidad / Fecha \_\_\_\_\_



**General**

Techo , Suspendido \_\_\_\_\_

inclinación máx. 90° \_\_\_\_\_

giro 265° \_\_\_\_\_

colores especiales \_\_\_\_\_

Baldaquín blanco tráfico \_\_\_\_\_

IP20 \_\_\_\_\_

791 lm \_\_\_\_\_

**LED**

3000 K \_\_\_\_\_

IRC  $\geq$  90 \_\_\_\_\_

L90 / 50000 h \_\_\_\_\_

MacAdam inicial  $\leq$  3 SDCM \_\_\_\_\_

R<sub>g</sub>: 100 , R<sub>f</sub>: 90 , R<sub>(1-15)</sub>: 87 \_\_\_\_\_

MR 0.59 \_\_\_\_\_

MDER 0.54 \_\_\_\_\_

**Óptico**

flood \_\_\_\_\_

ángulo de haz 44° \_\_\_\_\_

**Eléctrico**

DALI-2 \_\_\_\_\_

sistema 11.2 W \_\_\_\_\_

inserto 8.4 W \_\_\_\_\_

500 mA \_\_\_\_\_

CP2 220-240V \_\_\_\_\_

sistema 71 lm/W<sup>1</sup> \_\_\_\_\_

inserto 94 lm/W<sup>2</sup> \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_

**Físico**


varilla 1500 mm con gancho \_\_\_\_\_

diámetro 47 mm \_\_\_\_\_

altura 110 mm \_\_\_\_\_

0.65 kg \_\_\_\_\_


## Distribución luminosa



flood 44°

h (m)	EO° (lx)	ø (m)
1	1470	0.82
2	370	1.64
3	160	2.45
4	90	3.27
5	60	4.09

## Diseño del producto



<sup>1</sup> incl. optical losses and the efficiency of the operating device (converter)

<sup>2</sup> incl. optical losses

## Instrucciones de montaje



## Calculadora de iluminación

