

ARY adjustable rod suspended

canopy trimless

049-5131518M 005-3512017 002-90732



Proyecto / Tipo

Notas

Cantidad / Fecha



220-240V

UGR

cd/m²

CRI

X-PERT

General

Techo , Suspendido

inclinación máx. 90°

giro 265°

negro , RAL9005 ¹

Baldaquín blanco tráfico

IP20

739 lm

LED

3000 K

IRC ≥ 90

L90 / 50000 h

MacAdam inicial ≤ 3 SDCM

R_g: 100 , R_f: 90 , R₍₁₋₁₅₎: 87

MR 0.59

MDER 0.54

Óptico

medium

beam angle 25°

P_{stLM} ≤ 1.0 ²

SVM ≤ 0.4 ²

Eléctrico

non atenuable

11.2 W

CP2 220-240V

66 lm/W

Físico

varilla 1500 mm

diameter 47 mm

altura 110 mm

0.59 kg

Orificio

diameter 65 mm

min. ceiling thickness 9 mm

max. ceiling thickness 25 mm

recessed depth 70 mm

¹ Código RAL
² Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



medium 25°

h (m)	E0° (lx)	ø (m)
1	3200	0.44
2	800	0.89
3	360	1.33
4	200	1.78
5	130	2.22

Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

