

ARY adjustable rod suspended

canopy trimless

049-5131517F 005-3512017 002-90733



Proyecto / Tipo _____

Notas _____

Cantidad / Fecha _____



General

Techo , Suspendido _____

inclinación máx. 90° _____

giro 265° _____

blanco , RAL9016 ¹ _____

Baldaquín blanco tráfico _____

IP20 _____

791 lm _____

LED

3000 K _____

IRC ≥ 90 _____

L90 / 50000 h _____

MacAdam inicial ≤ 3 SDCM _____

R_g: 100 , R_f: 90 , R₍₁₋₁₅₎: 87 _____

MR 0.59 _____

MDER 0.54 _____

Óptico

flood _____

beam angle 44° _____

PstLM ≤ 1.0 ² _____

SVM ≤ 0.4 ² _____

Eléctrico

DALI-2 _____

11.2 W _____

CP2 220-240V _____

71 lm/W _____

1 DALI Addr. _____

Físico

varilla 1500 mm _____

diameter 47 mm _____

altura 110 mm _____

0.61 kg _____

Orificio

diameter 65 mm _____

min. ceiling thickness 9 mm _____


max. ceiling thickness 25 mm _____

recessed depth 130 mm _____

¹ Código RAL

² Valor del producto continente a plena carga (no atenuado)



Distribución luminosa



flood 44°

h (m)	E0° (lx)	ø (m)
1	1470	0.82
2	370	1.64
3	160	2.45
4	90	3.27
5	60	4.09

Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

