

ARY adjustable rod suspended

canopy trimless


049-5131418F 005-3512017 002-90733



Proyecto / Tipo _____

Notas _____

Cantidad / Fecha _____



General

Techo , Suspendido

inclinación máx. 90°

giro 265°

negro , RAL9005 ¹

Baldaquín blanco tráfico

IP20

688 lm

LED

2700 K

IRC ≥ 90

L90 / 50000 h

MacAdam inicial ≤ 3 SDCM

R_g: 99 , R_r: 91 , R_{t(1-15)}: 89

MR 0.54

MDER 0.49

Óptico

flood

beam angle 44°

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Eléctrico

DALI-2

11.2 W

CP2 220-240V

61 lm/W

1 DALI Addr.

Físico

varilla 1500 mm

diameter 47 mm

altura 110 mm

0.61 kg

Orificio

diameter 65 mm

min. ceiling thickness 9 mm


max. ceiling thickness 25 mm

recessed depth 130 mm

¹ Código RAL

² Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



flood 44°

h (m)	E0° (lx)	ø (m)
1	1280	0.82
2	320	1.64
3	140	2.45
4	80	3.27
5	50	4.09

Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

