

# ARY rod suspended

canopy trimless

049-5221418M 005-3511017 002-90733



Proyecto / Tipo
Notas
Cantidad / Fecha



## General

Techo , Suspendido
negro , RAL9005 <sup>1</sup>
Baldaquin blanco tráfico
IP20
642 lm

## LED

2700 K
IRC ≥ 90
L90 / 50000 h
MacAdam inicial ≤ 3 SDCM
R <sub>g</sub> : 99 , R <sub>f</sub> : 91 , R <sub>f(1-15)</sub> : 89
MR 0.54
MDER 0.49

## Óptico

medium
beam angle 25°
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>

## Eléctrico

DALI-2
11.2 W
CP2 220-240V
57 lm/W
1 DALI Addr.

## Físico

varilla 1500 mm con gancho
diameter 47 mm
altura 110 mm
0.66 kg

## Orificio

diameter 65 mm
min. ceiling thickness 9 mm
max. ceiling thickness 25 mm
recessed depth 130 mm

<sup>1</sup> Código RAL  
<sup>2</sup> Valor del producto continente a plena carga (no atenuado)


## Distribución luminosa



medium 25°

h (m)	EO° (lx)	ø (m)
1	2780	0.44
2	690	0.89
3	310	1.33
4	170	1.78
5	110	2.22

## Diseño del producto



## Instrucciones de montaje



## Calculadora de iluminación

