

ARY cable suspended

canopy trim

049-5211418M 005-3521018 002-90732



Proyecto / Tipo

Notas

Cantidad / Fecha



220-240V

UGR

cd/m²

CRI

X-PERT

General

Techo , Suspendido

negro , RAL9005 ¹

Baldaquin negro intenso

IP20

642 lm

LED

2700 K

IRC ≥ 90

L90 / 50000 h

MacAdam inicial ≤ 3 SDCM

R_g: 99 , R_r: 91 , R_{t(1-15)}: 89

MR 0.54

MDER 0.49

Óptico

medium

beam angle 25°

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Eléctrico

non atenuable

11.2 W

CP2 220-240V

57 lm/W

Físico

suspensión 2000 mm con gancho

diameter 47 mm

altura 110 mm

0.57 kg

Orificio

diameter 65 mm

min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 70 mm

¹ Código RAL
² Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



medium 25°

h (m)	E0° (lx)	ø (m)
1	2780	0.44
2	690	0.89
3	310	1.33
4	170	1.78
5	110	2.22

Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

