

ARY cable suspended

canopy trim

049-5211417M 005-3521017 002-90732



Proyecto / Tipo
Notas
Cantidad / Fecha



220-240V
UGR
cd/m ²
CRI
X-PERT

General

Techo , Suspendido
blanco , RAL9016 ¹
Baldaqin blanco tráfico
IP20
642 lm

LED

2700 K
IRC ≥ 90
L90 / 50000 h
MacAdam inicial ≤ 3 SDCM
R _g : 99 , R _f : 91 , R _{f(1-15)} : 89
MR 0.54
MDER 0.49

Óptico

medium
beam angle 25°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Eléctrico

non atenuable
11.2 W
CP2 220-240V
57 lm/W

Físico

suspensión 2000 mm con gancho
diameter 47 mm
altura 110 mm
0.58 kg

Orificio

diameter 65 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 70 mm

¹ Código RAL
² Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



medium 25°

h (m)	E0° (lx)	ø (m)
1	2780	0.44
2	690	0.89
3	310	1.33
4	170	1.78
5	110	2.22

Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

