

# ARY adjustable rod suspended

canopy trimless

049-513151XM 005-3512017 002-90732



Proyecto / Tipo \_\_\_\_\_

Notas \_\_\_\_\_

Cantidad / Fecha \_\_\_\_\_



220-240V

265°

90°

UGR ≤ 10

cd/m² ≤ 1500

CRI ≥ 90

X-PERT

## General

Techo , Suspendido

inclinación máx. 90°

giro 265°

colores especiales

Baldaquín blanco tráfico

IP20

739 lm

## LED

3000 K

IRC ≥ 90

L90 / 50000 h

MacAdam inicial ≤ 3 SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 90 , R<sub>f(1-15)</sub>: 87

MR 0.59

MDER 0.54

## Óptico

medium

beam angle 25°

PstLM ≤ 1.0<sup>1</sup>

SVM ≤ 0.4<sup>1</sup>

## Eléctrico

non atenuable

11.2 W

CP2 220-240V

66 lm/W

## Físico

varilla 1500 mm

diameter 47 mm

altura 110 mm

0.59 kg

## Orificio

diameter 65 mm


min. ceiling thickness 9 mm

max. ceiling thickness 25 mm

recessed depth 70 mm

<sup>1</sup> Valor del producto continente a plena carga (no atenuado)

## Distribución luminosa



medium 25°

h (m)	E0° (lx)	ø (m)
1	3200	0.44
2	800	0.89
3	360	1.33
4	200	1.78
5	130	2.22

## Diseño del producto



## Instrucciones de montaje



## Calculadora de iluminación

